

IP SURVEILLANCE SYSTEM



Network Camera Outdoor Enclosures

D-Link SecuriCam network camera enclosures provide a cost-effective solution for protecting D-Link's network cameras from the rigors of outdoor use.

The fixed enclosures include heavy-duty, angle-adjustable mounting brackets that can be used for securing the camera on a vertical or horizontal surface. These enclosures maximize the full potential of D-Link's network cameras for outdoor installations.

DCS-45

- IP66 Certified
- Water Resistance

DCS-50

- IP66 Certified
- Water Resistance
- Dust-Proof
- Built-in Power Supply

DCS-60

- IP44 Certified
- Water Resistance
- Dust-Proof
- Built-in Power Supply
- Heater & Blower

DCS-70

- IP66 Certified
- Water Resistance
- Dust-Proof
- Built-in Power Supply
- Heater & Blower
- Dome Type

Network Camera Selection Matrix

Model	10/100Mbps LAN Ports	802.11g 54Mbps 2.4GHz	802.3af PoE	Camera Type	Sensor	Lens Type	Day / Night Lens	Optical Zoom	Built-in Microphone	2-Way Audio	Sensor I/O Interface	Motorized Pan / Tilt	Motion Detection	Video Output to 3GPP	Samba Client for NAS	CF Card Slot
DCS-3110	✓		✓	Fixed	1.3 Megapixel CMOS Sensor	C/CS Mounted	✓ (with optional IR Lens)		✓	✓	✓		✓	✓	✓	✓
DCS-3410	✓		✓	Fixed	CCD Sensor	C/CS Mounted	✓ (with optional IR Lens)		✓	✓	✓		✓	✓	✓	
DCS-3415	✓		✓	Fixed	Sony Progressive CCD	Fixed		18X	✓	✓	✓		✓	✓	✓	✓
DCS-3420	✓	✓		Fixed	CCD Sensor	C/CS Mounted	✓ (with optional IR Lens)		✓	✓	✓		✓			
DCS-5300	✓			PTZ	CCD Sensor	Fixed			✓	✓	✓	✓	✓			
DCS-5300G	✓	✓		PTZ	CCD Sensor	Fixed			✓	✓	✓	✓	✓			
DCS-5610	✓		✓	PTZ	Sony Progressive CCD	Fixed		2.6X	✓	✓	✓	✓	✓	✓	✓	✓
DCS-6110	✓		✓	Dome	Progressive CMOS Sensor	Fixed							✓	✓	✓	
DCS-6111	✓		✓	Dome	WDR Progressive CMOS Sensor	Fixed	✓		✓	✓			✓			✓
DCS-6620	✓			PTZ	CCD Sensor	Fixed		10X	✓	✓	✓	✓	✓			
DCS-6620G	✓	✓		PTZ	CCD Sensor	Fixed		10X	✓	✓	✓	✓	✓			

STORAGE

Network Attached Storage (NAS) Enclosures

D-Link Network Attached Storage (NAS) enclosures enable the addition of disk storage devices to the network for sharing documents, files and digital media such as music, video and photographs. NAS enclosures are ideal for server deployment in office and business settings, and can add up to four internal SATA drives on a per need basis to fulfill storage requirements as the business grows. Remote access to files via the Internet is also possible through the built-in FTP server. Administrators can set access privileges for users, groups or folders according to their respective rights.



DNS-323 | External Power Supply | 2-Bay | Built-in Torrent Client

10/100/1000BASE-T x 1
USB Port to Printer or UPS x 1

- Support SATA Standard Drive
- Support Standard, JBOD, RAID 0,1
- Scheduled Backup
- Quota Management
- Built-in FTP Server
- Built-in UPnP AV Server
- Built-in Print Server
- Remote Backup

DNS-343 | External Power Supply | 4-Bay | OLED Display Screen

10/100/1000BASE-T x 1
USB Port to Printer or UPS x 1

- Support SATA II Standard Drive
- Support Standard, JBOD, RAID 0,1,5
- Scheduled Backup
- Quota Management
- Built-in FTP Server
- Built-in UPnP AV Server
- Built-in Print Server
- Remote Backup

DNS-346 | External Power Supply | 4-Bay | OLED Display Screen

10/100/1000BASE-T x 1
USB Port to Printer or UPS x 1

- Support SATA Standard Drive
- Support Standard, JBOD, RAID 0,1,5
- Scheduled Backup
- Quota Management
- Built-in FTP Server
- Built-in UPnP AV Server
- Built-in Print Server
- Pure NAS & iSCSI

Storage Area Network (SAN) Arrays

DSN-2100, DSN-3200 and DSN-3400 series Storage Area Network (SAN) arrays are designed to provide reliable network data storage solution for entry-level and SMB segments using the 10Gbit iSCSI System-on-a-Chip (SoC). These SAN arrays can be easily implemented as nearline storage or as a supplement to the primary backup and recovery devices.

DSN-2100 series is able to handle over 80,000 I/Os per second and capable of supporting 8TBs raw capacity using 1TB hard drives, while DSN-3200 and DSN-3400 series are able to handle over 65,000 I/Os per second and support 15TBs raw capacity using 1TB hard drives.

DSN-1100-10 | Internal Power Supply | 5 Real Trays

10/100/1000BASE-T x 4

- RAID Support
- SATA-II
- CHAP Authentication
- iSCSI
- up to 5TB capacity

DSN-2100-10 | Internal Power Supply | 8 Real Trays

10/100/1000BASE-T x 4

- RAID Support
- SATA-II
- CHAP Authentication
- iSCSI
- up to 8TB capacity

DSN-3200-10 | Internal Power Supply | 15 Real Trays

10/100/1000BASE-T x 8

- RAID Support
- SATA-II
- CHAP Authentication
- iSCSI
- up to 15TB capacity

DSN-3400-10 | Internal Power Supply | 15 Real Trays

10-Gigabit XFP x 1

- RAID Support
- SATA-II
- CHAP Authentication
- iSCSI
- up to 15TB capacity

Accessories

Product Model	Description
DSN-010	Single Real Tray
DSN-030	Power Supply for xStack Storage
DSN-040	Fan for xStack Storage
DSN-050	Battery for xStack Storage