

**D-Link** BUILDING NETWORKS FOR PEOPLE Product Announcement

DKVM-4U

Date: Nov 3, 2005

Product Description:	4 Port USB KVM Switch
Revision:	A1
Availability:	Now
Picture:	D-Link 2 - 4 - VeA Pot - D Turter to the second
Why Sell This Product:	Not just PS/2 keyboards and mice. There are now more USB keyboards and mice in the market, so putting more USB KVM switches out there too. The last USB KVM switch (the DKVM-2U) that we released had 2 ports, and was aimed at home and SOHO users. This one has 4 ports and is targeted at server rooms.
Key Features:	<ul> <li>4 KVM Ports</li> <li>Allows Control of 4 USB Style PCs From Single Keyboard, Mouse &amp; Monitor</li> <li>Supports VGA, SVGA &amp; Multisync monitors</li> <li>Supports Video Resolution 2048 x 1536 (Bandwidth Up to 400MHz)</li> <li>Supports USB Keyboard &amp; Mouse</li> <li>Keyboard &amp; Mouse Emulation for Error-Free Boot-Up</li> <li>Supports Microsoft IntelliMouse &amp; Microsoft IntelliMouse Explorer</li> <li>PC Selection Via Push Button or Hot Keys</li> <li>Audible Feedback When Switching</li> <li>Auto Scan Mode</li> <li>LED Indicator for Each PC</li> <li>Auto Recall of CAPS LOCK, NUM LOCK &amp; SCROLL LOCK Status for Each PC</li> <li>No Driver Required</li> <li>Bus Power, No AC Power Adapter Required</li> </ul>
Technical Details:	Connectors to Computers - 4 DB-15 HDDB video connectors (to computers' monitor ports) - 4 USB 2.0 Type B connectors (to computers' USB ports) Connectors to Console - DB-15 HDDB video connector (to console monitor) - USB Type A connector (to console USB keyboard) - USB Type A connector (to console USB mouse) Computer Selection (Manually switching back and forth among 4 computers) - Through push button - Through push button - Through hot keys - Switching confirmation: buzzer sound Hot Key Menu Functions Emission (EMI) - FCC Class B - CE - C-Tick O.S. Support
	- Microsoft Windows 98SE, ME, NT, 2000, XP, NT 2003 - Linux Red Hat



EMI/EMC Depert		لکا ا				
EMI/EMC Report		<u> </u>			Tick No	
	ØFCC No.       □ VCCI No.         □ CTR-21 No.       □ C-Tick No.         □ FDA No.       □ R&TTE No.         □ IC No       □ Others					
Safety	□ IC No □ Others □ TUV No □ UL No □ CSA No.					
Salety	□ CB No □ Others					
Packaging Style	□ Clamshell □ White Box ☑ Gift Box □ Bulk □ Brown Box □ Others					
Packaging Contents:	DKVM-4U KVM Switch					
Fackaging contents.	<ul> <li>DKVM-40 KVM Switch</li> <li>QIG</li> </ul>					
	• 2 in1 USB KVM Cable x 2					
UPC Code:		UPC code Part Number				
01 0 00de.				er	-	
	790069	285745	BKVM4UA1			
	790069	285714	EKVM4UA1			
	790069	285738	IKVM4UA1			
	790069	285721	TKVM4UA1			
Units Per Carton:	For USA		For EU	F	or WW	
	10		10	10		
Cartons Per Pallet:	For USA		For EU		or WW	
	Air:24, Sea:	36	Air: 36, Sea:36	A	ir:24:, Sea: 36	
Dimensions and Weight:	Box: □ 237x168x36mm (Type A) □ 225x150x75mm (Type B) □ 269x162x65mm (Type C) ☑ 274x208x68mm (Type D) □ 274x208x118mm (Type D1) □274x208x138mm (Type D2)					
	□ 288x245x66mm (Type E) , Others, <u>1.2</u> kg					
	<b>Carton:</b> 435*350*298 mm, <u>13</u> kg					
	Pallet: (by Air) <u>1220x1020x 1342</u> mm, <u>330</u> kg (for USA)					
	<u>1200x1100x 1803</u> mm, <u>486</u> kg (for EU) <u>1200x1100x 1342</u> mm, <u>330</u> kg (for WW) (by Sea) <u>1220x1020x1803</u> mm, <u>486</u> kg (for USA)					
	(by Se		<u>20x 1803 _ mm, 486 _</u> )0x 1803 _ mm, <u>486 _</u>			
			00x 1803 mm, 480			
				<u>- ng (ibi</u>	,	
	INTRASTAT weight: 0.9 kg (Box) Packing material weight (Box):					
	- Paper: <u>0278</u> kg - Plastic: <u>0.013</u> kg					
	- Mixed: <u>0</u> kg					



## **Product Announcement**

	PMA
Product Class	5 Digital Home(080)
ltem Group	5-111 Peripheral
Sub Group	5-216 KVM Switch
Intelligence	304 Un-Managed
Tech.(Features)	5-436 USB 2.0
Layer	606 N/A
Application	502 Home/SOHO
Q'ty	1
Interface 1     Interface	702 Host 🔽
Net Interface	5-800 Others
Port NO.	4
Interface 2	
Interface	
Net Interface	
Port NO.	