

# **Wireless G Network Storage Enclosure**

## Add Hard Drive to Wireless Network

- Open Bay for 3.5-Inch Hard Drive
- 2 USB Ports for Attachment of Additional Hard Drives or Flash Drives
- Gigabit Port For Ethernet Network Connection
- Built-in 802.11g WLAN for Wireless User Access
- Wireless Access Point Functionality

#### **FEATURES**

#### **Hardware Configurations**

- 3.5-Inch Internal Hard Drive Installable in Open Bay
- Additional External Hard Drives/Flash Drives Attachable to 2 USB 2.0 Ports

#### **Network Connection**

- 1000BASE-T Gigabit Port for Connection to Ethernet Network or Router
- Built-in 802.11g Wireless LAN Functions as Access Point
- WPA & WPA-PSK Wireless Security

#### **Applications**

- Good for Recording of Live Surveillance Footage From Network Security Cameras
- Automatic (Scheduled) Downloads From Web or FTP Sites

### **Drive Access/Management**

- User Account Creation & User-Definable Folder Permissions
- Built-in FTP Server for Remote File Access
- Scheduled Full or Incremental Backups
- Automatic Email Notifications

#### Installation/Setup

- Web-Based Configuration/Management
- UPnP AV Compliant for Compatibility With Other Media Devices





he D-Link MediaLounge DSM-G600 wireless G network storage enclosure connects your existing hard drive to the home or office network. With the DSM-G600, you can conveniently share documents, files, and digital media such as music, video, and photos with everyone on your home or office network. You can free up disk space on the computer and organize data on your network with the DSM-G600 wireless G network storage enclosure.

The DSM-G600 can be used with an internal 3.5-inch ATA/IDE hard drive, giving you the flexibility of choosing the storage capacity required for your network. And with 2 additional high-speed USB ports, you can expand your storage capabilities even further as your network needs grow by adding your own external USB drives.

In addition, the DSM-G600 also functions as an wireless access point. You can create an 802.11g wireless network when you attach the DSM-G600 to your wired router.

By adding your own hard drives to the DSM-G600, you can conveniently store, retrieve, and share digital content with everyone on your home or office network. As a central storage location for data, the DSM-G600 is an organized solution for the network. Since the DSM-G600 is visible and available to everyone on the network, you can use it to share files or collaborate on projects.







### **Technical Specifications**

#### Standards

- IFFF 802 3
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.11b ■ IEEE 802.11g

#### **Hard Drive Type Support**

- All Variants of ATA/IDE up to ATA/133
- 3.5-inch Internal

#### **Device Ports**

- 1 10/100/1000 Gigabit Ethernet Port
- 2 USB 2.0 Ports

#### Wireless Security

- WPA
- WPA-PSK
- 64/128-bit WEP data encryption

#### Wireless transmit Power

15dBm (32mW) (using 2dBi gain antenna)

- Receiver Sensitivity

  54Mbps OFDM, 10% PER: -68 dBm
- 48Mbps OFDM, 10% PER: -68 dBm
- 36Mbps OFDM, 10% PER: -75 dBm
- 24Mbps OFDM, 10% PER: -79 dBm
- 18Mbps OFDM, 10% PER: -82 dBm
- 12Mbps OFDM, 10% PER: -84 dBm
- 11Mbps CCK 8% PER: -82 dBm
- 9Mbps 0FDM, 10% PER: -87 dBm ■ 6Mbps 0FDM, 10% PER: -88 dBm
- 5.5Mbps CCK, 8% PER: -85 dBm
- 2Mbps QPSK, 8% PER: -86 dBm
- 1Mbps BPSK, 8% PER: -89 dBm

#### Antenna

2.0dB Gain external antenna with reverse SMA connector

#### Wireless Signal Range \*

- Indoors: up to 100 m (328 ft)
- Outdoors: up to 400 m (1,312 ft)
- \* Environmental factors may adversely affect signal range

#### **Drive Management**

- Format
- Scandisk
- Email Alerts

#### **Device Management**

Web-based, using Internet Explorer v.6 or Netscape Navigator v.7 or other Java-enabled browsers

#### Diagnostic LED

- Power
- I AN
- HDD
- HDD Full USB
- WI AN

### **Physical & Environmental**

#### **Power Voltage**

- Output: 12V, 3A
- Max power: 36w, 100-240V

#### **Operating Temperature**

0° to 55°C

#### Storage Temperature

-20° to 70 °C

#### Humidity

5% to 90% (non-condensing)











### Dimensions


19.53 x 17.68 x 6.12 cm (7.69 x 6.96 x 2.41 inches)

### Weight

 $0.77\bar{kg}$  (1.7 lbs)

#### Certifications

- FCC Part 15 Class B
- CE
- C-Tick



### **D-Link Worldwide Offices**

U.S.A. Canada Europe (U. K.) Germany France Netherlands Belgium Italy Sweden Denmark Norway Finland Spain **Portugal** Czech Republic Switzerland Greece

TEL: 1-800-326-1688 TEL: 1-905-8295033 TEL: 44-20-8731-5555 TEL: 49-6196-77990 TEL: 33-1-30238688 TEL: 31-10-282-1445 TEL: 32(0)2-517-7111 TEL: 39-02-2900-0676 TEL: 46-(0)8564-61900 TEL: 45-43-969040 TEL: 47-99-300-100 TEL: 358-9-2707 5080

TEL: 41-(0)-1-832-11-00

TEL: 30-210-9914 512

FAX: 1-866-743-4905 FAX: 1-905-8295223 FAX: 44-20-8731-5511 FAX: 49-6196-7799300 FAX: 33-1-30238689 FAX: 31-10-282-1331 FAX: 32(0)2-517-6500 FAX: 39-02-2900-1723 FAX: 46-(0)8564-61901 FAX: 45-43-424347 FAX: 47-22-309580 FAX: 358-9-2707-5081 TEL: 34-93-4090770 FAX: 34-93-4910795 TEL: 351-21-8688493 TEL: 420-(603)-276-589

Hungary Singapore Australia India Turkey Egypt Israel **LatinAmerica** Brazil South Africa Russia China FAX: 41(0)-1-832-11-01 Taiwan **Headquarters** FAX: 30-210-9916902

Luxemburg TEL: 32-(0)2-517-7111 Poland TEL: 48-(0)-22-583-92-75 TEL: 36-(0)-1-461-30-00 TEL: 65-6774-6233 TEL: 61-2-8899-1800 TEL: 91-022-26526696 Middle East (Dubai) TEL: 971-4-3916480 TEL: 90-212-289-56-59 TEL: 202-414-4295 TEL: 972-9-9715700 TEL: 56-2-232-3185 TEL: 55-11-218-59300 TEL: 27-12-665-2165 TFI · 7-095-744-0099 TEL: 86-10-58635800 TEL: 886-2-6600-0123

TEL: 886-2-6600-0123

FAX: 32-(0)2-517-6500 FAX: 48-(0)-22-583-92-76 FAX: 36-(0)-1-461-30-09 FAX: 65-6774-6322 FAX: 61-2-8899-1868 FAX: 91-022-26528914 FAX: 971-4-3908881 FAX: 90-212-289-76-06 FAX: 202-415-6704 FAX: 972-9-9715601 FAX: 56-2-232-0923 FAX: 55-11-218-59322 FAX: 27-12-665-2186 FAX: 7-095-744-0099 #350 FAX: 86-10-58635799 FAX: 886-2-6600-8168 FAX: 886-2-6600-9898

Rev 02 (Dec 2005)

Specifications subject to change without prior notice D-Link is a registered trademark and medialounge is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors