



2-PORT USB 3.0 EXPRESSCARD

SUPER SPEED USB 3.0

Transfer files up to 10 times faster than through USB 2.0

COMPATIBLE WITH YOUR DEVICES

Backwards compatibility with USB 2.0 and 1.1 ensures that you can connect all your USB devices to your PC

SIMPLE TO INSTALL

Just slide it into your laptop's ExpressCard slot to instantly add 2 USB 3.0 ports



BLAZING USB 3.0 SPEED

Connect your laptop to USB 3.0 devices at blazing speeds of up to 5 Gbps - up to 10 times faster than USB 2.0. You can back up your photos, music, and HD movies to an external storage device faster than ever before.

PLUG AND PLAY CONNECTIVITY

Just slide the card into your ExpressCard slot and run the Setup CD; it's that simple to add 2 USB 3.0 ports to your PC.

CONNECT ALL YOUR PERIPHERALS

Backward compatibility with USB 2.0 and USB 1.1 mean that you can connect any USB device to the DUB-1320. If you need more ports, you can connect additional USB hubs to connect up to 127 devices.

WHAT THIS PRODUCT DOES

The DUB-1320 2-Port USB 3.0 ExpressCard adds 2 USB 3.0 ports to your notebook, allowing you to connect peripherals such as external storage, digital cameras, printers, and more.



TECHNICAL SPECIFICATIONS

INTERFACE

- ExpressCard 34
- PCI Express 2.0 x1
- 2 downstream USB Type A (female) ports

STANDARDS

- USB specification version 3.0
- USB specification version 2.0
- USB specification version 1.1 1
- USB specification version 1.0
- OHCI (Open Host Controller Interface)
- EHCI (Enhanced Host Controller Interface)
- PCI Express 2.0

DATA RATES

- SuperSpeed: 4.8 Gbps
- High Speed: 480 Mbps
- Full Speed: 12 Mbps
- Low Speed: 1.5 Mbps

CONNECTIVITY

- Up to 127 devices by cascading multiple hubs

SYSTEM REQUIREMENTS

- Windows® 7/Vista/XP SP3 or higher
- Available ExpressCard 34 or 54 slot

SUPPLIED POWER

- Bus Power Only:
 - Maximum 100 mA per port
- With External Power Adapter:
 - Maximum 900 mA per port

POWER

- External power adapter 5 V / 2.5 A

DIMENSIONS (L x W x H)

- 117.19 x 40.54 x 14.55 mm (4.6 x 1.6 x 0.6 inches)

WEIGHT

- 40.5 grams

OPERATING TEMPERATURE

- 0 to 40 °C (32 to 104 °F)

STORAGE TEMPERATURE

- -20 to 60 °C (-4 to 140 °F)

OPERATING HUMIDITY

- 0% to 80% (non-condensing)

PACKAGE CONTENTS

- D-Link 2-Port USB 3.0 ExpressCard
- Power adapter

CERTIFICATIONS

- USB-IF
- WHQL
- FCC
- CE

¹ Using a USB 1.1 port will affect device performance.

² Maximum transfer rate based on USB 3.0 specifications. Actual data throughput will vary.

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, actual product appearance may differ than that depicted on the packaging.



D-Link Corporation
No. 289 Xinhu 3rd Road, Neihu, Taipei 114, Taiwan
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved.
Release 01 (July 2010)