



— DCS-5300

## Pan/Tilt Internet Camera

### With Integrated Web Server & Motion Detection

The DCS-5300 Internet Camera is an advanced security system that allows you to watch and listen remotely. This full-featured camera connects to an Ethernet network in a building or campus, and to broadband Internet. It provides you with high-quality video and audio. Equipped with built-in Web server, a micro-phone for listening, and a motor for rotation, this camera can be panned and tilted remotely, accessed and controlled from any PC/Notebook over a local network or through the Internet. With motion detected image recording, time-saving trigger event playback, alert message and powerful software for multi-camera monitoring and management, this camera provides a comprehensive system for convenient surveillance from both a local site or remotely from anywhere in the world.

#### Stand-alone System With Integrated Web Server

This Internet Camera comes with a built-in CPU and Web server, providing a low-cost solution for security needs. Its integrated Web server eliminates the need to connect the camera to a computer. Once installed, you use the built-in IP address to gain access to the camera, view live streaming video, and make changes to camera settings.

#### Web-based Remote Access

You can install your camera at home then view the images from anywhere in the world on a computer running Internet Explorer. Directly connected to the Internet without going through any computer, this camera is simple to install and easily integrates with your network environment.

#### Automatic Camera Movement to View Different Angles

The camera is mounted on a motor for rotation to capture images from different angles. From a remote site, you can manually rotate the camera's horizontal and vertical movements. The camera movement angles can also be set up for automatic panning and tilting in rotation according to a pre-set timing.

#### Multi-Camera Monitoring

Surveillance software is included to let you view up to 16 cameras on a single computer screen at one central location. Images can be recorded to your computer's hard drive manually or according to a

pre-set schedule. The camera can be connected to external alarms and sensors, and you can set up automated email alerts for sending through the Internet to alarm you instantly of all unusual happenings.

#### Motion Detected Recording

Instead of recording 24 hours a day, 7 days a week, images can also be recorded only when motions are detected. This saves disk space and eliminates the time wasted to view unnecessary images. Images can be directly archived straight to your computer hard drive or to a Network Attached Storage. Playback consumes little time with triggered event browsing and fast database searching.

#### High-Quality Video & Sound

The camera uses MPEG-4 Short Header Mode to stream live video at up to 30 frames per second for real-time viewing. A built-in microphone allows you to listen while watching live images. The camera can also be attached to an external, more powerful microphone and a TV in a private room, where you can monitor streaming images and listen to surveillance sound.

#### Ethernet Connection

The camera provides a 10/100BASE-TX port for connection to an Ethernet network without going through any PC for cost-effective surveillance in and around a building. This Ethernet port can also be used to connect to a broadband Internet via a home gateway router.

### Key Features

- Stand-alone Internet camera with CPU & RAM, no need to attach to PC
- Built-in rotation motor for manual or auto camera pan/tilt with wide movement angle support
- Sound surveillance through built-in microphone or powerful external microphone connected to MIC jack
- Simple to use with real-time monitoring in Windows environment
- Local access through Ethernet
- Remote access from web browser
- Supports DDNS and UPnP for easy configuration in a network environment
- Surveillance software to control up to 16 cameras
- Motion detection triggered recording or scheduled recording to administrator's hard disk or Network Attached Storage (and VCR) for each camera
- Smart playback with triggered event browsing, fast database searching
- Auto alarm in different ways
- AV cable connection to local TV for monitoring
- MPEG4 short header mode high compression ratio
- Connects to external devices for alarm-based event recording when trigger is activated
- Implemented for intruder detection with still image capture & e-mail notice
- Powerful software for image capture & video recording
- Web-based configuration, remote utility provided

# DCS-5300

## Technical Specifications

## Internet Camera

### Hardware

- 24-bit RGB, 320 x 240 resolution
- 1/4-inch color CCD sensor, interlace scan mode
- Pan range +/- 135 degrees
- Tilt range +90 to -45 degrees
- Automatic Gain control (AGC) 24dBi
- Automatic Exposure (AE)
- Automatic White Balance
- Electronics shutter 1/60 to 1/15000 second
- Minimum illumination 2.5lux @ f1.4
- Lens mounting: standard CS mount type lens, 6.0mm, f1.8

### Image (Video Setting)

- MPEG4 short header mode compression
- Compression ratio: 5 levels
- Adjustable image size, quality and bit-rate
- Time stamp and text overlay

### Communication

- 1 RJ-45 auto-sensing 10/100BASE-TX port to connect to 10/100Mbps Ethernet
- Supported communication protocols: HTTP, FTP, TCP/IP, UDP, SMTP, DHCP, Telnet, NTP, DDNS, UPnP and DNS

### Viewing System Requirement

Internet Explorer 5.x or above

### Audio

8kbps

### Security

- Administrator and user group protected
- 15 digits password authentication

### LED Indicators

- System power and status indicators
- Network link and speed indicators

### Alarms and I/O

- Motion detection (activity detection)
- Periodical image transfers through e-mail and upload to a server, using FTP
- 1 sensor input (12Vdc to 48Vdc/50mA)
- 1 relay output (Max. 24Vdc/1A, 125Vac/0.5A)

### Management and Software Update

- Configuration and system log can be accessed via Web browser and FTP application remotely
- Allows new firmware version updates via TCP/IP network

### Channel Display (6 layouts)

Maximum 16 views

### Recording Modes

- Manual Control
- Event-driven
- Scheduled recording

### Playback Schemes

Date, Time interval, and event triggering with preview for every camera

### Playback Control Modes

Play, Stop, Pause, Fast Forward, Slow Forward, Pull-bar, Zoom in, Zoom out

## Physical & Environmental

### Power

- Through switching external power adapter (AC input range 100 to 240 V, 50/60Hz)
- DC Output: 12VDC, 1.5A

### Dimensions

110.5mm (H) x 103.5mm (W) x 103mm (D) (camera only, mounted motor included)

### Weight

343 grams (camera only, mounted motor included)

### Operation Temperature

5° to 55°C

### Storage Temperature

-10° to 60 °C

### Humidity

20% to 90% non-condensing

### Emission (EMI)

- FCC Class B
- CE Class B

### Safety

LVD (EN60950)

### Box Includes

- DCS-5300 Internet Camera
- Remote control
- A/V cable
- Cat. 5 Ethernet cable
- Manual & software on CD-ROM
- Stand & mounting brackets
- External power adapter
- Quick Installation Guide



## Ordering Information

### DCS-5300

Pan/Tilt Internet Camera with 10/100BASE-TX network interface

Please specify your order as follows:

### BDCS5300W

NDCS-5300W/A

NDCS-5300W/B

NDCS-5300W/E

NDCS-5300W/N

For USA (USA packaging)

NTSC TV format support, US standard power adapter

NTSC TV format support, UK standard power adapter

NTSC TV format support, EU standard power adapter

NTSC TV format support, China & Australia standard power adapter

PDCS-5300W/A

PDCS-5300W/B

PDCS-5300W/E

PDCS-5300W/N

PAL TV format support, US standard power adapter

PAL TV format support, UK standard power adapter

PAL TV format support, EU standard power adapter

PAL TV format support, China & Australia standard power adapter

# D-Link®

Specifications subject to change without prior notice.  
D-Link is a registered trademark and SecurCAM is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

### U.S.A

### Canada

### Europe

### Germany

### France

### Benelux

### Italy

### Iberia

### Sweden

### Norway

### Denmark

### Finland

### Singapore

### Australia

### Japan

### China

### India

### Middle East (Dubai)

### Turkey

### Egypt

### Israel

### Chile

### Brasil

### South Africa

### Russia

### Taiwan

### D-Link Corp.

TEL: 1-714-885-6000

TEL: 1-905-8295033

TEL: 44-20-8731-5555

TEL: 49-6196-77990

TEL: 33-1-30238688

TEL: 31-10-282-1445

TEL: 39-2-2900-0676

TEL: 34-93-4090770

TEL: 46-(0)8564-61900

TEL: 47-22-309075

TEL: 45-43-969040

TEL: 358-9-2707-5080

TEL: 65-6774-6233

TEL: 61-2-8899-1800

TEL: 81-3-5434-9678

TEL: 86-10-8518-2533

TEL: 91-022-652-6696

TEL: 9714-8834234

TEL: 90-212-335-2553

TEL: 202-414-4295

TEL: 972-9-9715700

TEL: 56-2-232-3185

TEL: 55-11-55039320

TEL: 27(0)1266-52165

TEL: 7-095-744-0099

TEL: 886-2-2910-2626

TEL: 886-2-2916-1600

FAX: 1-866-743-4905

FAX: 1-905-8295223

FAX: 44-20-8731-5511

FAX: 49-6196-7799300

FAX: 33-1-30238689

FAX: 31-10-282-1331

FAX: 39-2-2900-1723

FAX: 34-93-4910795

FAX: 46-(0)8564-61901

FAX: 47-22-309085

FAX: 45-43-424347

FAX: 358-9-2707-5081

FAX: 65-6774-6322

FAX: 61-2-8899-1868

FAX: 81-3-5434-9868

FAX: 86-10-8518-2250

FAX: 91-022-652-8914

FAX: 9714-8834394

FAX: 90-212-335-2500

FAX: 202-415-6704

FAX: 972-9-9715601

FAX: 56-2-232-0923

FAX: 55-11-55039321

FAX: 27(0)1266-52186

FAX: 7-095-744-0099#350

FAX: 886-2-2910-1515

FAX: 886-2-2914-6299



RECYCLABLE

Rev. 01 (Dec. 2003)