



AirPlus Xtreme G™

Up to
15X
Faster

Total 802.11
Super G™
ATHEROS

108
Mbps

WiFi®
CERTIFIED **b/g**

DI-624

802.11g High Speed Wireless Cable/DSL Router With 4-Port Switch

The DI-624 AirPlus Xtreme G is a high-speed 2.4GHz 802.11g wireless broadband Internet Gateway Router with a built-in 4-port Fast Ethernet Switch. It incorporates high-speed wireless LAN with speeds of up to 108Mbps Turbo mode. This router lets you quickly and easily share DSL or cable modem Internet connection, with or without the network wires. With advanced functions traditionally found in business-class routers also built inside, this router gives the business and home a cost-effective way to install a secure and fast network with bottleneck-free link to the outside world.

Simplified, Cost-saving Broadband Internet Connection

As the most basic function, the router allows you to share your broadband line and cable/DSL modem in your office or home. To let everybody logon, this device automatically creates and assigns an IP number for each user, simplifying every one's logon operation.

Ready Connection

With built-in wireless LAN connections and 10/100Mbps switch, this router provides ready connection for workstations and servers, with or without the network wires. These built-in functions save you the cost and trouble of installing a separate wireless access point and Ethernet switch.

Up to 108Mbps Speed on 2.4GHz Frequency Band *

With transmission speeds of up to 108Mbps (Turbo mode) on the popular 2.4GHz public frequency, the DI-624 is an ideal solution for bandwidth intensive WLAN applications. In a typical working environment with multiple users accessing the network at the same time, the DI-624 can operate at 15 times the throughput of the normal 802.11b wireless LAN equipment.

Compatible With 802.11b

The DI-624's compatibility with earlier standard 802.11b wireless LAN equipment as well as third-party 802.11g wireless gears means that you do not need to change your existing network to maintain connectivity. This ensures a smooth upgrade to higher speeds while maintaining an ability to communicate with your existing equipment, providing a valuable protection for your previous investments in network hardware.

Firewall and VPN Protection

The router provides NAT protection for your office and home users from Internet intruders and hacker attacks. For tele-commuters or anyone who needs to transmit sensitive information more securely, the router supports multiple concurrent VPN sessions IPsec, L2TP and PPTP pass-through. The router also blocks and re-directs certain ports to limit the services that outside users can access your network. Virtual Server Mapping is used to re-task services to multiple servers. The router can be set to allow separate FTP, Web, and Multiplayer game servers to share the same Internet-visible IP address while still protecting your servers and workstations from hackers.

DMZ Host to Open Public Domain

You can configure any of the built-in LAN ports to function as a DMZ port. ADMZ setting can be applied to a single client (such as a Web server) behind the router to fully expose it to the Internet and ensure complete Internet application compatibility even if the specific port is not known. This allows you to set up web sites and e-commerce business from your office while maintaining protection for the rest of your office LAN.

Access Control

Access to the router from your home/office can be set based on users' MAC addresses and IP addresses. Parental control to filter certain URL and block web sites can be set through URL keywords and domain names. Outbound link scheduling can be made in conjunction with NTP. The router supports the Network Time Protocol (NTP), allowing you to install a time server behind the router to synchronize time for your network environment. This protects you from the risks inherent in obtaining Internet, minimizes security risks from the outside, and maximizes timing accuracy on your network.

* 108Mbps Turbo mode when operating with other AirPlus Xtreme G products.

Wireless Security

To protect transmitted data in the air, the router employs the enhanced 152-bit industry-standard WEP (Wired Equivalent Privacy) encryption protocol. WPA (Wi-Fi Protected Access) provides users a higher level of security for data and communications than has previously been available.

UPnP Enabled for Compatibility

The router is designed for easy and robust connectivity among heterogeneous standards-based network devices. Computers can communicate directly with the router for automatic opening and closing of UDP/TCP ports to take full advantage of security provided without sacrificing functionality of on-line applications.

Features

- 108Mbps Turbo mode high-speed wireless broadband Internet access
- Real throughput 15X faster than 802.11b
- PPPoE support for xDSL saves ISP charge through dial-out connection-on-demand
- Built-in 4-port Fast Ethernet switch for ready server connection
- Detachable dipole antenna for easy replacement
- Virtual Private Network (VPN) security for multiple tele-commuters
- WPA network security
- 64/128/152-bit WEP data encryption for wireless users
- DHCP server for automatic user IP assignment
- Firewall protection with NAT, DMZ and Virtual Server Mapping support
- User access control through MAC/IP address filtering
- Parental control with URL filtering and domain blocking
- Network schedule control with Network Time Protocol support
- Easy web-based management from any browser

* 108Mbps Turbo mode when operating with other AirPlusXtremeG products.

Technical Specifications**Router****WAN Interface**

- RJ-45 10BASE-T/100BASE-TX port
- Supports PPPoE for dial-out connection

LAN Interfaces

- 802.11g wireless LAN (54 Mbps)
- 4 RJ-45 10BASE-T/100BASE-TX ports

Routed Packet Type

IP packets

VPN Support

- IPSec pass-through
- L2TP pass-through
- PPTP pass-through

Internet Gateway Functions

- Network Address Translation (NAT)
- DHCP server (for automatic IP assignment)

Number of DMZ Ports

1 port (user-assignable to any LAN port)

Number of Virtual Server Mappings

10 entries

IP Number Self-identification

Through DHCP client

Configuration & Management

Web-based configuration

Built-in Wireless LAN**Standards**

802.11g wireless LAN

Media Access Control Protocol

CSMA/CA with ACK

Network Architecture Types

Infrastructure mode

Frequency Range

2.4 - 2.4835 GHz

Operating Channels

- US (FCC): 11
- Europe (ETSI): 13
- Canada (D)C): 11

Network Transfer Rate/Modulation Technique

- 802.11b:
 - 11Mbps, 5.5Mbps: CCK
 - 2Mbps: DQPSK
 - 1Mbps: DBPSK
- 802.11g:
 - 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps, 6Mbps: OFDM (Orthogonal Frequency Division Multiplexing)

Receive Sensitivity (for 802.11b)

- 1Mbps: -90dBm
- 2Mbps: -90dBm
- 5.5Mbps: -86dBm
- 11Mbps: -82dBm

Receive Sensitivity (for 802.11g)

- 6Mbps: -90dBm
- 9Mbps: -89dBm
- 12Mbps: -86dBm
- 18Mbps: -82dBm
- 24Mbps: -79dBm
- 36Mbps: -76dBm
- 48Mbps: -72dBm
- 54Mbps: -68dBm

Transmit Output Power (for 802.11b)

1Mbps, 2Mbps, 5.5Mbps, 11Mbps: 18dBm

Transmit Output Power (for 802.11g)

- 6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps: 18dBm
- 48Mbps, 54Mbps: 17dBm

Antenna

2dBi Gain detachable antenna with reverse SMA connector

Operation Range

- Indoors: up to 100 meters (328 feet)*
- Outdoors: up to 400 meters (1,312 feet)*

* Environmental factors may adversely affect range

Security

- 64/128/152-bit WEP data encryption
- WPAEAP, WPA PSK

Built-in Fast Ethernet Switch Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation

Supported Functions

- Full/half duplex (per port)
- MDI/MDIX auto uplink (per port)

Transmission Method

Store-and-forward

MAC Address Learning

Automatic update

Physical & Environmental**Diagnostic LEDs**

- Power
- WAN
- WLAN
- 1, 2, 3, 4 LAN ports

Power Input

- DC 5V 2.5A
- Through external AC power adapter

Dimensions

233 x 165 x 35 mm (9.25 x 6.5 x 1.38 inches)

Weight

907 grams (2.0 lb.)

Operating Temperature

0° - 55°C (32° - 131° F)

Humidity

95% maximum non-condensing

EMI Certification

- FCC Class B
- CE Class B

Safety Certification

- UL



LISTED
ITE
E141136
66F9



ACN 052 202 838

**Ordering Information****Wireless Broadband Internet Gateway Router****DI-624**

- 1 RJ-45 0BASE-T/100BASE-TX port (for xDSL/cable modem connection)
- 802.11g wireless LAN
- 4 RJ-45 10BASE-T/100BASE-TX switch ports

Please specify one of the following after the model number:

DI-624/ANA	Includes US standard AC power adapter, North America frequency
DI-624/BEU	Includes U.K. standard AC power adapter, EU frequency
DI-624/EEU	Includes EU standard AC power adapter, EU frequency
DI-624/CN	Includes China standard AC power adapter, EU frequency
DI-624/NEU	Includes Australia standard AC power adapter, EU frequency
DI-624/ENA	Includes EU standard adapter, North America frequency
DI-624/UNA	Includes no AC power adapter, North America frequency
DI-624/UEU	Includes no AC power adapter, EU frequency

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademarks and AirPlus XtremeG is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Norway	TEL: 47-99-300-100	FAX: 47-22-309580
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795
Portugal	TEL: 351-21-8688493	
Czech Republic	TEL: 420-(603)-276-589	
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902
Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
India	TEL: 91-022-26526696	FAX: 91-022-26528914
Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Latin America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
China	TEL: 86-10-58635800	FAX: 86-10-58635799
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
Headquarters	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299