



Product Highlights

HIGH POWER AND SPEED

Dual core (900MHz),
Gigabit Ethernet ports

Wi-Fi 6 (802.11ax)

Less network congestion and faster
speed – total wireless connection rate
up to 1500Mbps¹

SECURITY

Multiple firewall functions, several
security standards for wireless
connection

IPV6 SUPPORT

All needed functions
for up-to-date networking



DIR-X1530

AX1500 Wi-Fi 6 EasyMesh Gigabit Router

Wireless Interface

Support of Wi-Fi 6 (802.11ax) standard provides faster speeds, greater capacity, and less network congestion for high-performance device-dense environments. It ensures connection of more devices and prevents weakening wireless connectivity by wall obstruction and interference from other appliances.

Using the DIR-X1530 device, you are able to quickly create a high-speed wireless network at home or in your office, which lets computers and mobile devices access the Internet virtually anywhere (within the operational range of your wireless network). Simultaneous activity of 2.4GHz band and 5GHz band allows performing a wide range of tasks. The router can operate as a base station for connecting wireless devices of the standards 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, and 802.11ax (at the wireless connection rate up to 1500Mbps¹).

Secure Wireless Connection

The router supports multiple functions for the wireless interface: several security standards (WEP, WPA/WPA2/WPA3), MAC address filtering, WPS, WMM.

In addition, the device is equipped with a button for switching the Wi-Fi network off/on. If needed, for example, when you leave home, you can easily switch the router's WLAN by pressing the button, and devices connected to the LAN ports of the router will stay online.

Advanced Capabilities of Wireless Network

The EasyMesh function is D-Link implementation of mesh networks designed to quickly connect several² devices into one transport network, for example, when it's required to provide high-quality Wi-Fi coverage without dead zones in living units of complicated planning or it's needed to create a large temporary Wi-Fi network for an outdoor event.

Multi-user MIMO technology allows to distribute the router's resources to let multiple wireless clients use the Wi-Fi network efficiently, keeping high rates for HD media streaming, lag-free gaming, and fast transfer of large files.

Transmit Beamforming technology allows to flexibly change the antennas' radiation pattern and to redistribute the signal directly to wireless devices connected to the router.

Support of guest Wi-Fi network allows you to create a separate wireless network with individual security settings and maximum rate limitation. Devices connected to the guest network will be able to access the Internet, but will be isolated from the devices and resources of the router's LAN.

¹ Up to 300Mbps for 2.4GHz and up to 1201Mbps for 5GHz.

² Up to 6 devices.

Security

The wireless router DIR-X1530 includes a built-in firewall. The advanced security functions minimize threats of hacker attacks and prevent unwanted intrusions to your network, and block access to unwanted websites for users of your LAN.

The SSH protocol support provides more secure remote configuration and management of the router due to encryption of all transmitted traffic, including passwords.

In addition, the router supports IPsec and allows to create secure VPN tunnels. Support of the IKEv2 protocol allows to provide simplified message exchange and use asymmetric authentication engine upon configuration of an IPsec tunnel.

The router also supports the SkyDNS web content filtering service, which provides more settings and opportunities for safer Internet experience for home users of all ages and for professional activities of corporate users.

Now the schedules are also implemented; they can be applied to the rules and settings of the firewall and used to reboot the router at the specified time or every specified time period and to enable/disable the wireless network and the Wi-Fi filter.

The new ad blocking function effectively blocks advertisements which appear during web surfing.

Easy configuration and update

You can configure the settings of the wireless router DIR-X1530 via the user-friendly web-based interface (the interface is available in two languages – in Russian and in English).

The configuration wizard allows you to quickly switch DIR-X1530 to one of the following modes: router (for connection to a wired or wireless ISP), access point, repeater, or client, and then configure all needed setting for operation in the selected mode in several simple steps.

Also DIR-X1530 supports configuration and management via mobile application for Android and iPhone smartphones.

You can simply update the firmware: the router itself finds approved firmware on D-Link update server and notifies when ready to install it.

Hardware	
Processor	RTL8198D (900MHz, dual core)
RAM	256MB, DDR3, built in processor
Flash	128MB, SPI NAND
Interfaces	10/100/1000BASE-T WAN port 3 10/100/1000BASE-T LAN ports
LEDs	- Power - Internet - WLAN 2.4G - WLAN 5G
Buttons	- WPS button to connect mesh network devices, set up wireless connection, and enable/disable wireless network - RESET button to restore factory default settings
Antenna	Four external non-detachable antennas (5dBi gain)
MIMO	2 x 2, MU-MIMO
Power connector	Power input connector (DC)
Mounting	- Desktop - Wall

Software	
WAN connection types	- PPPoE - IPv6 PPPoE - PPPoE Dual Stack - Static IPv4 / Dynamic IPv4 - Static IPv6 / Dynamic IPv6 - PPPoE + Static IP (PPPoE Dual Access) - PPPoE + Dynamic IP (PPPoE Dual Access) - PPTP/L2TP + Static IP - PPTP/L2TP + Dynamic IP - IPIP6 in DSLite mode 6in4 6to4 6rd
Network functions	- DHCP server/relay - Advanced configuration of built-in DHCP server - Stateful/Stateless mode for IPv6 address assignment, IPv6 prefix delegation - Automatic obtainment of LAN IP address (for access point/repeater/client modes) - DNS relay - Dynamic DNS - Static IPv4/IPv6 routing - IGMP Proxy - RIP - Support of UPnP - Support of VLAN - WAN ping respond - Support of SIP ALG - Support of RTSP - WAN failover - LAN/WAN conversion - Autonegotiation of speed, duplex mode, and flow control / Manual speed and duplex mode setup for each Ethernet port - Built-in UDPXY application - Port mirroring
Firewall functions	- Network Address Translation (NAT) - Stateful Packet Inspection (SPI) - IPv4/IPv6 filter - MAC filter - URL filter - Ad blocking function - DMZ - Virtual servers - Built-in SkyDNS web content filtering service

Software	
VPN	• IPsec/PPTP/L2TP/PPPoE pass-through • PPTP/L2TP servers • PPTP/L2TP tunnels • L2TP over IPsec • GRE/EoGRE/EoIP/IPIP tunnels • IPsec tunnels • Transport/Tunnel mode • IKEv1/IKEv2 support • DES encryption • NAT Traversal • Support of DPD (Keep-alive for VPN tunnels)
Management and monitoring	• Local and remote access to settings through SSH/TELNET/WEB (HTTP/HTTPS) • Bilingual web-based interface for configuration and management (Russian/English) • Support of D-Link Assistant application for Android and iPhone smartphones • Notification on connection problems and auto redirect to settings • Firmware update via web-based interface • Automatic notification on new firmware version • Saving/restoring configuration to/from file • Support of logging to remote host • Automatic synchronization of system time with NTP server and manual time/date setup • Ping utility • Traceroute utility • TR-069 client • Schedules for rules and settings of firewall, automatic reboot, and enabling/disabling wireless network and Wi-Fi filter • Automatic upload of configuration file from ISP's server (Auto Provision) • Configuration of action for hardware buttons

Wireless Module Parameters	
Standards	• IEEE 802.11ax • IEEE 802.11ac Wave 2 • IEEE 802.11a/b/g/n • IEEE 802.11w
Frequency range <i>The frequency range depends upon the radio frequency regulations applied in your country</i>	• 2400 ~ 2483.5MHz • 5150 ~ 5350MHz • 5650 ~ 5850MHz
Wireless connection security	• WEP • WPA/WPA2 (Personal/Enterprise) • WPA3 (Personal) • MAC filter • WPS (PBC/PIN)
Advanced functions	• EasyMesh function • Support of client mode • WMM (Wi-Fi QoS) • Information on connected Wi-Fi clients • Advanced settings • Guest Wi-Fi / support of MBSSID • Limitation of wireless network rate • Periodic scan of channels, automatic switch to least loaded channel • Support of 5GHz TX Beamforming • Autonegotiation of channel bandwidth in accordance with environment conditions (20/40 Coexistence) • CoovaChilli authentication portal • Support of OFDMA technology • Support of TWT technology
Wireless connection rate	• IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, and 54Mbps • IEEE 802.11b: 1, 2, 5.5, and 11Mbps • IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, and 54Mbps • IEEE 802.11n (2.4GHz/5GHz): from 6.5 to 300Mbps (MCS0–MCS15) • IEEE 802.11ac (5GHz): from 6.5 to 867Mbps • IEEE 802.11ax (5GHz): from 6.5 to 1201Mbps
Transmitter output power <i>The maximum value of the transmitter output power depends upon the radio frequency regulations applied in your country</i>	• Less than 20dBm (100mW)

Wireless Module Parameters	
Receiver sensitivity	802.11a (typical at PER < 10% (1000-byte PDUs) at room temperature 25 °C) -94dBm at 6Mbps -76dBm at 54Mbps 802.11b (typical at PER = 8% (1000-byte PDUs) at room temperature 25 °C) -96dBm at 1Mbps -89dBm at 11Mbps 802.11g (typical at PER < 10% (1000-byte PDUs) at room temperature 25 °C) -92dBm at 6Mbps -72dBm at 54Mbps 802.11n (typical at PER = 10% (1000-byte PDUs) at room temperature 25 °C) 2.4GHz, HT20 5GHz, HT20 -91dBm at MCS0/8 -93dBm at MCS0/8 -72dBm at MCS7/15 -74dBm at MCS7/15 2.4GHz, HT40 5GHz, HT40 -90dBm at MCS0/8 -90dBm at MCS0/8 -71dBm at MCS7/15 -71dBm at MCS7/15 802.11ac (typical at PER = 10% (1000-byte PDUs) at room temperature 25 °C) VHT20 -93dBm at MCS0 -68dBm at MCS8 VHT40 -90dBm at MCS0 -63dBm at MCS9 VHT80 -87dBm at MCS0 -60dBm at MCS9 802.11ax (typical at PER = 10% (1000-byte PDUs) at room temperature 25 °C) HE20 -90dBm at MCS0 -65dBm at MCS11 HE40 -87dBm at MCS0 -62dBm at MCS11 HE80 -84dBm at MCS0 -59dBm at MCS11

Physical Parameters	
Dimensions (L x W x H)	194 x 139 x 55 mm (7.64 x 5.47 x 2.17 in)
Weight	300 g (0.66 lb)

Operating Environment	
Power	Output: 12V DC, 1A
Temperature	- Operating: from 0 to 40 °C - Storage: from -20 to 65 °C
Humidity	- Operating: from 10% to 90% (non-condensing) - Storage: from 5% to 95% (non-condensing)

Delivery Package	
	- Router DIR-X1530 - Power adapter DC 12V/1A - Ethernet cable - Quick Start Guide