

Flexible Choices

- 24 or 48 10/100 Mbps ports
- 4 or 2 combo Gigabit copper/SFP uplinks for connections either in cabinets or metropolitan areas
- Adjustable switch databases for different applications

Reliability

- 802.1D/802.1w/802.1s Spanning Tree
- Loopback Detection (LBD)
- Ethernet Ring Protection Switching (ERPS)
- Redundant Power Supply (RPS)

Security

- Multi-Layer Access Control List (ACL)
- IP-MAC-Port Binding (IMPB)
- D-Link Safeguard Engine
- DHCP Server Screening
- BPDU Attack Protection
- ARP Spoofing Prevention

AAA

- 802.1X
- Web-based Access Control (WAC)
- MAC-based Access Control (MAC)
- Compound Authentication
- Identity-Driven Policies
- Microsoft® NAP support
- RADIUS Accounting

Triple Play

- IGMP/MLD Snooping
- IGMP Snooping Multicast (ISM) VLAN
- Port/Flow/VLAN/Queue-based Bandwidth Control
- Granular Bandwidth Control down to 1 Kbps
- Three Color Marker
- Traffic Shaping

OAM

- 802.3ah Link OAM
- 802.1ag, ITU-T Y.1731 Service OAM
- Port/Flow Mirroring, RSPAN
- DHCP Auto Configuration
- sFlow

Advanced Routing

- Open Shortest Path First (OSPF)
- Policy-based Routing (PBR)
- Protocol Independent Multicast (PIM)

xStack L3 Managed Fast Ethernet Switches



The DES-3810 Series 24 and 48-port switches are the latest additions to the D-Link xStack family of next-generation, high-end, multi-service Layer 3 switches. The DES-3810-28 provides 24 10/100 Mbps Fast Ethernet ports and 4 combo 1000Base-T/SFP Gigabit Ethernet ports. The DES-3810-52 provides 48 10/100 Mbps Fast Ethernet ports, 2 1000Base-T and 2 combo 1000Base-T/SFP Gigabit Ethernet ports. The Fast Ethernet ports allow users to connect to other LAN access switches. The combo ports provide users with a much higher level of flexibility for dedicated trunk connections between devices or core switches.

Enhanced Network Reliability

The DES-3810 Series targets enterprise/campus and customers who require a high level of network security and maximum uptime. The DES-3810-28 and DES-3810-52 both support an external redundant power supply so that continued operation is assured. They also include other features, such as 802.1D Spanning Tree (STP), 802.1w Rapid Spanning Tree (RSTP), and 802.1s Multiple Spanning Tree (MSTP), Loopback Detection (LBD), and Broadcast Storm Control, that enhance network resilience. The G.8032 Ethernet Ring Protection Switching (ERPS) function minimizes the recovery time to 50 ms. For load sharing and redundancy backup in switch cascading/server attachment configuration, the DES-3810 Series provides dynamic 802.3ad Link Aggregation Port Trunking.

Comprehensive Security

The DES-3810 Series provides users with the latest security features such as Multi-layer and Packet Content Access Control Lists (ACL), Storm Control, and IP-MAC-Port Binding (IMPB) with DHCP Snooping. The IP-MAC-Port Binding feature allows administrators to bind a source IP address with an associated MAC and also define the port number to enhance user access control. With the DHCP Snooping feature, the switch automatically learns IP/MAC pairs by snooping DHCP packets and saving them to the IMPB white list. In addition, the D-Link Safeguard Engine identifies and prioritizes "CPU interested" packets to prevent malicious traffic from interrupting normal network flows and to protect switch operation.

Identity Driven Network Policies

The DES-3810 Series supports authentication mechanisms such as 802.1X, Web-based Access Control (WAC), and MAC-based Access Control for strict access control and easy deployment. After authentication, individual policies such as VLAN membership, QoS policies, and ACL rules can be assigned to each host. In addition, the switch also supports Microsoft® NAP (Network Access Protection). NAP is a policy enforcement technology that allows customers to protect network assets from unhealthy computers by enforcing compliance with network health policies.

Traffic Management for Triple Play Services

The DES-3810 Series implements a rich set of multilayer QoS/CoS features to ensure that critical network services like VoIP, video conference, IPTV, and IP surveillance are served with priority. Three Color Marker and Traffic Shaping guarantee the quality of these services when the network is busy. With L2/L3 Multicast support, the DES-3810 shows its ability to handle growing IPTV applications. The Host-based IGMP/MLD Snooping allows multiple multicast subscribers per physical interface and ISM VLAN sends multicast streams in a multicast VLAN to save bandwidth in the backbone network. The ISM VLAN profiles allow users to bind/replace the pre-defined multicast registration information to subscriber ports quickly and easily.

Proactive, Effective Network Management

To uphold enterprise customers' Service Level Agreements (SLA), service providers must reduce the Mean Time to Repair (MTTR) and increase service availability. Ethernet OAM features address these challenges and enable service providers to offer carrier-grade services. The DES-3810 Series supports industry-standard OAM tools, including IEEE 802.3ah, IEEE802.1ag, and ITU-T Y.1731. Connectivity Fault Management (CFM) provides tools to monitor and troubleshoot end-to-end Ethernet networks, allowing service providers to check connectivity, isolate network issues, and identify customers affected by network issues.

IPv6 Features

- IPv6 Neighbor Discovery (ND)
- IPv6 Management
- IPv4/v6 Dual Stack
- IPv6 Tunneling
- IPv6 Dynamic Routing
- IPv6 Ready Logo Phase 2

VPN Tunnel Service

- VLAN Translation
- Selective Q-in-Q
- L2 Protocol Tunneling (L2PT)
- Label Distribution Protocol (LDP)
- Virtual Private Wire Service (VPWS)

xStack L3 Managed Fast Ethernet Switches

High Performance Routing

The DES-3810 Series supports hardware-based, wire speed L3 routing functions. For small networks, inter-VLAN routing, static routing, and Routing Information Protocol (RIP) provide an easy way to configure your L3 routing environment. For mid-to-large networks, Open Shortest Path First (OSPF) is supported for better routing performance. The Policy-based Routing (PBR) allows administrators to control the direction of dynamic routing either for load balance or security reasons.

For L3 multicasting, the DES-3810 Series supports rich Protocol Independent Multicast (PIM) protocols including PIM Sparse Mode (PIM-SM), PIM Dense Mode (PIM-DM), PIM Source-Specific Multicast (PIM-SSM), and PIM Sparse-Dense mode.

Interoperable with IPv4 and IPv6

The DES-3810 Series is fully compliant with the future IPv6 networks. It supports remote IPv6 manageability from telnet, HTTP, or SNMP. It also supports the IPv6 dynamic routing protocols such as RIPng. Additionally, this device supports IPv4/v6 dual stack and IPv6 tunneling functions, allowing the DES-3810 to play the role of a bridge between IPv4 and IPv6 networks.

To create secure IPv6 networks, the DES-3810 Series supports IPv6 ACL, IPv6 RADIUS, DHCPv6 Snooping, and Neighbor Discovery (ND) Snooping functions to protect the network from illegal IPv6 clients.

VPN Tunnel Service For Enterprises

The DES-3810 Series can also be used as a telecom access switch. It supports many advanced features such as VLAN translation, Selective Q-in-Q, and Virtual Private Wire Service (VPWS) that allows users to create L2 VPN tunnels through the telecom MPLS backbone. With L2 Protocol Tunneling (L2PT), the DES-3810 provides L2 transparency to business subscribers through the ISP network helping reduce IT expenses by centralizing network management.



xStack L3 Managed Fast Ethernet Switches

Technical Specifications		DES-3810-28	DES-3810-52
General	Interface	24 10/100 BASE-T ports 4 Combo 10/100/1000 BASE-T / 100/1000 SFP ports	48 10/100 BASE-T ports 2 1000 SFP ports 2 Combo 10/100/1000 BASE-T / 100/1000 SFP ports
	Optional Redundant Power Supply	DPS-200	DPS-200
	Console Port	RJ-45	RJ-45
	Out-of-band Management Port	RJ-45	RJ-45
Performance	Switching Capacity	12.8 Gbps	17.6 Gbps
	64-byte Max. Packet Forwarding Rate	9.5 Mpps	13.1 Mpps
	CPU	800 MHz	800 MHz
	Packet Buffer	1.5 MB	3 MB
	Flash Memory	32 MB	32 MB
	DRAM	256 MB	256 MB
Physical	MTBF (Hours)	382,307 hours	375,189 hours
	Acoustic	0 dB (fanless)	< 33 °C, 32.6 dB > 33 °C, 42.3 dB
	Heat Dissipation	79.85 BTU/h	123.78 BTU/h
	Power Input	100 to 240 V AC, 50 to 60 Hz Internal Universal Power Supply	100 to 240 V AC, 50 to 60 Hz Internal Universal Power Supply
	Max Power Consumption	23.4 watts	38.8 watts
	Dimensions (W x D x H)	441 x 260 x 44 mm (17.36 x 10.24 x 1.73 inches)	441 x 309 x 44 mm (17.36 x 12.17 x 1.73 inches)
	Weight	3.1 kg (6.83 pounds)	4.1 kg (9.04 pounds)
	Ventilation	Fanless	1 Smart Fan (Default low speed)
	Operating Temperature	0 to 50 °C (32 to 122 °F)	0 to 50 °C (32 to 122 °F)
	Storage Temperature	-40 to 70 °C (-40 to 158 °F)	-40 to 70 °C (-40 to 158 °F)
	Operating Humidity	10% to 90% non-condensing	10% to 90% non-condensing
	Storage Humidity	5% to 90% RH	5% to 90% RH
	Emission (EMI)	FCC Class A, CE, C-Tick, VCCI	FCC Class A, CE, C-Tick, VCCI
	Safety	cUL, CB	cUL, CB
Certifications	IPv6 Ready Logo Phase 2	IPv6 Ready Logo Phase 2	



xStack L3 Managed Fast Ethernet Switches

Software Features

- L2 Features**
 - Stackability
 - Virtual Stacking
 - D-Link Single IP Management (SIM)
 - Up to 32 units per Virtual Stack
 - MAC Address Table: 16K
 - Flow Control
 - 802.3x Flow Control
 - HOL Blocking Prevention
 - Jumbo Frames up to 10,240 bytes
 - Spanning Tree Protocols
 - 802.1D STP
 - 802.1w RSTP
 - 802.1s MSTP
 - BPDU Filtering
 - Root Restriction
 - Loopback Detection
 - Ethernet Ring Protection Switching (ERPS)
 - 802.3ad Link Aggregation
 - Max. 14 groups per device / 8 ports per group
 - Port Mirroring
 - One-to-One
 - Many-to-One
 - Flow-based
 - RSPAN
 - L2 Protocol Tunneling
 - L2 Multicasting**
 - IGMP Snooping
 - IGMP v1/v2/v3 Snooping
 - Supports 1024 IGMP groups
 - Port/Host-based Fast Leave
 - MLD Snooping
 - MLD v1/v2 Snooping
 - Supports 1024 groups
 - Port/Host-based Fast Leave
 - IGMP/MLD Proxy Reporting
 - VLAN**
 - VLAN Group
 - Max. 4K VLAN groups
 - GVRP
 - Supports 4K dynamic VLAN groups
 - 802.1Q Tagged VLAN
 - Port-based VLAN
 - 802.1v Protocol VLAN
 - Double VLAN (Q-in-Q)
 - Port-based Q-in-Q
 - Selective Q-in-Q
 - VLAN Translation for single/double tagged packets
 - Voice VLAN
 - MAC-based VLAN
 - Subnet-based VLAN**
 - ISM VLAN
 - VLAN Trunking
 - Private VLAN
 - L3 Features**
 - Max. 256 IPv4 Interfaces, 32 IPv6 Interfaces
 - ARP Proxy
 - Loopback Interface
 - IGMP/MLD Proxy
 - VRRP
 - IPv6 Tunneling
 - Static
 - ISATAP
 - GRE
 - 6to4
 - IPv6 Neighbor Discovery (ND)
 - L3 Routing**
 - Up to 7,286 IPv4 external routes
 - Up to 1,821 IPv6 external routes
 - Up to 3,575 IPv4 host routes
 - Up to 1,821 IPv6 host routes
 - 256 static routing entries for IPv4, 128 entries for IPv6
 - Policy-based Routing
 - Route Redistribution
 - RIP v1/v2
 - RIPng
 - OSPF
 - Supports OSPF v2
 - OSPF Passive Interface
 - Stub/NSSA Area
 - OSPF Equal Cost Route
 - L3 Multicasting**
 - Up to 1,024 hardware IPv4 multicast groups
 - Up to 256 hardware IPv6 multicast groups
 - IGMP Filtering
 - Up to 60 IGMP filtering profiles, 128 ranges per profile
 - IGMP v1,v2,v3
 - DVMRP v3
 - PIM-DM
 - PIM-SM
 - PIM-SSM
 - PIM Sparse-Dense Mode
 - MPLS**
 - LDP
 - MPLS L2 VPN
 - VPWS
 - QoS (Quality of Service)**
 - IEEE 802.1p
 - DSCP
 - 8 Queues per Port
 - Queue Handling
 - Strict Priority
 - Weighted Round Robin (WRR)
 - Strict + WRR
 - CoS based on
 - Switch Port
 - VLAN ID
 - 802.1p Priority Queues
 - MAC Address
 - IPv4/v6 Address
 - DSCP
 - Protocol Type
 - IPv6 Traffic Class
 - IPv6 Flow Label
 - TCP/UDP Port
 - User-defined Packet Content
 - Supports Following Actions for Flows
 - Remark 802.1p Priority Tag
 - Remark TOS/DSCP Tag
 - Bandwidth Control
 - Flow Statistics
 - Three Color Marker
 - trTCM
 - srTCM
 - Bandwidth Control
 - Port-based (Ingress/Egress, Min. Granularity 64 Kbps)
 - Flow-based (Ingress/Egress, Min. Granularity 1 Kbps)
 - Per Egress Queue Bandwidth Control (Min. Granularity 64 Kbps)
 - Time-based QoS
 - Access Control List (ACL)**
 - Up to 1,024 Ingress Access Rules
 - Up to 500 Egress Access Rules
 - ACL based on
 - 802.1p Priority
 - VLAN ID
 - MAC Address
 - Ether Type
 - IPv4/v6 Address
 - DSCP
 - Protocol Type
 - TCP/UDP Port Number
 - IPv6 Traffic Class
 - IPv6 Flow Label
 - User-defined Packet Content
 - ACL Statistics
 - Time-based ACL
 - CPU Interface Filtering
 - SSH v2/ SSH v6
 - SSL v1/v2/v3
 - Port Security
 - Broadcast/Multicast/Unicast Storm Control
 - Traffic Segmentation
 - IP-MAC-Port Binding (IPv4/v6)
 - ARP Packet Inspection
 - IP Packet Inspection
 - DHCP Snooping
 - IPv6 ND Snooping
 - Supports up to 500 address binding entries per device
 - D-Link Safeguard Engine
 - NetBIOS/NetBEUI Filtering
 - DHCP Server Screening
 - BPDU Attack Protection
 - ARP Spoofing Prevention
 - L3 Control Packet Filtering
- AAA**
 - 802.1X
 - Port-based Access Control
 - Host-based Access Control
 - Authentication Database Failover
 - Identity-Driven Policy (VLAN, ACL, or QoS) assignment
 - Web-based Access Control (WAC)
 - Port-based Access Control
 - Host-based Access Control
 - Dynamic VLAN Assignment
 - Authentication Database Failover
 - Identity-driven Policy (VLAN, ACL, or QoS Assignment)
 - MAC-based Access Control (MAC)
 - Port-based Access Control
 - Host-based Access Control
 - Authentication Database Failover
 - Identity-driven Policy (VLAN, ACL, or QoS) assignment
 - Japan Web-based Access Control (JWAC)
 - Port-based Access Control
 - Host-based Access Control
 - Authentication Database Failover
 - Identity-driven Policy (VLAN, ACL, or QoS Assignment)
 - Compound Authentication
 - Guest VLAN
 - Microsoft® NAP
 - 802.1X NAP support
 - DHCP NAP support
 - RADIUS
 - TACACS
 - XTACACS



xStack L3 Managed Fast Ethernet Switches

Software Features

- TACACS+
- RADIUS Accounting
- 3 Level User Account
- Trusted Host

Operation, Administration & Management (OAM)

- Loopback Diagnostics
- Cable Diagnostics
- 802.3ah Ethernet Link OAM
- D-Link Unidirectional Link Detection (DULD)
- Broadcast/Multicast/Unicast Storm Control
- Dying Gasp
- 802.1ag Connectivity Fault Management (CFM)
- ITU-T Y.1731
- Optical Transceiver Digital Diagnostic Monitoring (DDM)

Green Features

- Power Saving by Link Status¹
- Power Saving by Cable Length¹
- Power Saving by LED Shut-Off
- Power Saving by Port Shut-Off
- Power Saving by System Hibernation

Management

- Web-based GUI (Supports IPv4/IPv6)
- Command Line Interface (CLI)
- Telnet Server(Supports IPv4/IPv6)
- Telnet Client(Supports IPv4/IPv6)
- TFTP Client(Supports IPv4/IPv6)
- FTP Client
- Remote Copy Protocol (RCP)
- PPPoE Circuit-ID Tag Insertion
- ZModem
- SNMP v1/v2c/v3
 - SNMP over IPv6
- SNMP Traps
- System Log
- SMTP
- RMON v1
 - Supports 1,2,3,9 groups

- RMON v2
- Supports ProbeConfig Group
- sFlow
- LLDP
- BootP/DHCP Client
- DHCP Auto-Configuration
- DHCP Relay (Support IPv4/v6)
- DHCP Relay Option 60, 61, 82
- DHCP Server
- Flash File System for multiple images and configurations
- CPU Monitoring
- DNS Relay
- SNTP
- Password Recovery
- Password Encryption
- Microsoft® NLB (Network Load Balancing)
- Ping (Supports IPv4/v6)
- Traceroute (Supports IPv4/v6)
- DLMS
- Switch Resource Management (SRM)

MIB

- RFC1065, 1066, 1155, 1156, 2578 MIB Structure
- RFC1212 Concise MIB Definitions
- RFC1213 MIB II
- RFC1215 MIB Traps Convention
- RFC1493 Bridge MIB
- RFC1157, 2571-2576 SNMP MIB
- RFC 1901-1908, 1442, 2578 SNMPv2 MIB
- RFC1757, 2819 RMON MIB
- RFC2021 RMONv2 MIB
- RFC1398, 1643, 1650, 2358, 2665 Ether-like MIB
- RFC2674, 4363 802.1p MIB
- RFC2233, 2863 Interface Group MIB
- RFC2618 RADIUS Authentication Client MIB
- RFC2620 RADIUS Accounting Client MIB
- RFC2866 RADIUS Accounting
- RFC2925 Ping & Traceroute MIB

- D-Link Private MIB
- RFC2787 VRRP MIB
- RFC1492 TACACS+
- RFC1724 RIPv2 MIB
- RFC1850 OSPF MIB
- RFC2932 IPv4 Multicast Routing MIB
- RFC2934 IP Forwarding Table MIB

Standard Compliance

- RFC768 UDP
- RFC791 IP
- RFC792 ICMPv4
- RFC2463, 4443 ICMPv6
- RFC793 TCP
- RFC826 ARP
- RFC1321, 2284, 2865, 2716, 3580, 3748 Extensible Authentication Protocol (EAP)
- RFC2571 SNMP Framework
- RFC2572 SNMP Message Processing and Dispatching
- RFC2573 SNMP Applications
- RFC2574 User-based Security Model for SNMPv3
- RFC1981 Path MTU Discovery for IPv6
- RFC2460 IPv6
- RFC2461, 4861 Neighbor Discovery for IPv6
- RFC2462, 4862 IPv6 Stateless Address Auto-configuration
- RFC2464 IPv6 over Ethernet and definition
- RFC3513 IPv6 Addressing Architecture
- RFC2893 IPv4/IPv6 dual stack function
- RFC3056 IPv6 Tunneling
- RFC2328, 3101 OSPF
- RFC1112, 2326, 3376 IGMP
- RFC3973 PIM-DM
- RFC4601 PIM-SM
- RFC3569 PIM-SSM
- RFC1112, 2236, 3376, 4605 IGMP Proxy
- RFC4541 Proxy Reporting
- RFC4363 802.1v
- RFC1027 ARP Proxy
- RFC2338 VRRP
- RFC1058, 1388, 1723, 2453 RIP
- RFC2475 Priority Queue Mapping
- RFC2475, 2598 Class of Service (CoS)
- RFC3315 DHCPv6 Relay
- RFC2597, 2598 QoS Flow Actions
- RFC2697, 2698 Three Color Marker
- RFC2246 SSL
- RFC3580 802.1X
- RFC2866 RADIUS Accounting
- RFC2138, 2139, 2865, 2618 RADIUS Auth for Mgmt Access
- RFC1492 TACACS+ Auth for Mgmt Access
- RFC2068, 2616 Web-based GUI
- RFC854 Telnet Server
- RFC1519 CIDR
- RFC 2474, 3168, 3260 Definition of the DS Field in the IPv4 and IPv6 Headers
- RFC783, 1350 TFTP Client
- RFC1157, 1901, 1908, 2570, 2574, 2575 SNMP
- RFC3164 System Log
- RFC2819 RMON v1
- RFC3176 sFlow
- RFC951, 1542, 2131, 3046 BOOTP/DHCP Client
- RFC2131 DHCP Server
- RFC1769 Time Setting
- RFC2821 SMTP
- RFC4250, 4251, 4252, 4253 SSH
- ITU-T Y.1731
- ITU-T G.8032
- IPv6 Ready Logo Phase 2 router mode
- SFF-8472 Optical Transceiver Digital Diagnostic Monitoring (DDM)

¹ For Gigabit ports

Ordering Information

DES-3810-28	24 10/100 BASE-T ports 4 combo 10/100/1000 BASE-T / 100/1000 SFP ports	DES-3810-52	48 10/100 BASE-T ports 2 1000 SFP ports 2 combo 10/100/1000 BASE-T / 100/1000 SFP ports
DES-3810-28-SE-LIC	DES-3810-28 Standard Image to Enhanced Image License	DES-3810-52-SE-LIC	DES-3810-52 Standard Image to Enhanced Image License

Optional Products

Optional SFP Transceivers

EM-310GT	SFP transceiver, 1000BASE-LX standard, single-mode fiber, max. distance 10 km, 3.3 V operating voltage
DEM-311GT	SFP transceiver, 1000BASE-SX standard, multi-mode fiber, max. distance 550 m, 3.3 V operating voltage
DEM-312GT2	SFP transceiver 1000BASE-SX standard, multi-mode fiber, max. distance 2 km, 3.3 V operating voltage
DEM-314GT	SFP transceiver, 1000BASE-LHX standard, single-mode fiber, max. distance 50 km, 3.3 V operating voltage
DEM-315GT	SFP transceiver, 1000BASE-ZX standard, single-mode fiber, max. distance 80 km, 3.3 V operating voltage
DEM-211	SFP transceiver, 100BASE-FX standard, up to 2 km multi-mode fiber cable distance, 3.3 V operating voltage
DEM-210	SFP transceiver, 100BASE-FX standard, up to 15 km single-mode fiber Cable distance, 3.3 V operating voltage

Optional WDM SFP Transceivers

DEM-330T	WDM SFP transceiver, 1000BASE-BX standard, single-mode fiber, max. distance 10 km, 3.3 V operating voltage, Tx wavelength 1550 nm, Rx wavelength 1310 nm
DEM-330R	WDM SFP transceiver, 1000BASE-BX standard, single-mode fiber, max. distance 10 km, 3.3 V operating voltage, Tx wavelength 1310 nm, Rx wavelength 1550 nm
DEM-331T	WDM SFP transceiver, 1000BASE-BX standard, single-mode fiber, max. distance 40 km, 3.3 V operating voltage, Tx wavelength 1550 nm, Rx wavelength 1310 nm
DEM-331R	WDM SFP transceiver, 1000BASE-BX standard, single-mode fiber, max. distance 40 km, 3.3 V operating voltage, Tx wavelength 1310 nm, Rx wavelength 1550 nm
DEM-220T	WDM SFP transceiver, 100BASE-BX standard, single-mode fiber, max. distance 20 km, Tx wavelength 1550 nm, Rx wavelength 1310 nm
DEM-220R	WDM SFP transceiver, 100BASE-BX standard, single-mode fiber, max. distance 20 km, Tx wavelength 1310 nm, Rx wavelength 1550 nm

Optional Redundant Power Supply System

DPS-200	60 watts redundant power supply
DPS-800	2-slot redundant power supply chassis
DPS-900	8-slot redundant power supply chassis

Optional Management Software

DV-600S	D-View 6.0 Network Management Software Standard Edition
DV-600P	D-View 6.0 Network Management Software Professional Edition

Optional Accessories

DRE-KIT019	Universal wall mount bracket
------------	------------------------------



D-Link Corporation
No. 289 Xinhui 3rd Road, Neihu, Taipei 114, Taiwan
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2013 D-Link Corporation. All rights reserved.
Release 05 (May 2013)