

Product Highlights

High Performance

Gigabit access ports and in-built 10 Gigabit uplinks provide high bandwidth connections for clients, servers, and storage

Flexible Software

Multiple software images provide a flexible approach to software management, allowing only the required features to be installed

High Availability

Up to 9 physical switches can be stacked to create a single virtual switch, providing fault tolerance and increasing network reliability



DGS-3630 Series

Layer 3 Stackable Managed Switches

Features

High Availability and Flexibility

- 20/44 10/100/1000BASE-T ports or 20 SFP ports
- 4 Combo 10/100/1000BASE-T/SFP ports
- 4 10 GbE SFP+ uplink ports
- Switch Resource Management (SRM) for flexible management of system resources
- 6 kV surge protection on all RJ-45 access ports

Reliability

- Redundant Power Supply (RPS) support
- IEEE 802.1D/802.1w/802.1s Spanning Tree
- Loopback Detection (LBD)
- Ethernet Ring Protection Switching (ERPS)

High Bandwidth Stacking

- Physical stack of up to 9 units, 432 GbE ports
- Supports long-distance stacking over fiber
- 80 Gbps per device physical stacking bandwidth

Operations, Administration, and Maintenance

- IEEE 802.3ah Ethernet First Mile (EFM)
- IEEE 802.1ag/ITU-T Y.1731 OAM

Easy Management

- RJ-45/mini-USB console port
- Management and alarm ports
- USB port for firmware and configuration files
- Easy-to-use web GUI
- Industry standard CLI

The DGS-3630 Series Layer 3 Stackable Managed Switches are a range of switches designed for Small Medium Businesses (SMBs), Small Medium Enterprises (SMEs), enterprises, and ISPs. They deliver high performance, flexibility, fault tolerance, and advanced software features for maximum return on investment. With Gigabit Ethernet SFP, 10 GbE SFP+, security features, and advanced Quality of Service (QoS), the DGS-3630 Series can act as core, distribution or access layer switches. High port densities, switch stacking, and easy management make the DGS-3630 Series suitable for a variety of applications.

Standard, Enhanced, and MPLS Images

The DGS-3630 Series is designed for use with three different software images: the Standard Image (SI), the Enhanced Image (EI), and the MPLS Image (MI). The Standard Image provides core SMB and SME functionality, such as L2 switching, entry-level routing, L2 multicast, advanced QoS, Operations, Administration, and Maintenance (OAM), and robust security features. The Enhanced Image supports full L3 routing for enterprise integration, including OSPF, BGP, VRF-Lite and L3 multicast. The MPLS Image offers VPN services for ISPs, including IS-IS and MPLS L2/L3 VPN. With multiple software images, only the required features need to be installed, providing a flexible approach to software management.

High Availability and Flexibility

The DGS-3630 Series includes stacking technology, which allows multiple switches to be combined to form a single physical or virtual stack. This increases redundancy over multiple physical units, simplifies management, and provides a single IP address to manage all members in the stack. Up to 9 switches can be combined using Direct Attach Cables to make up to 432 Gigabit Ethernet ports available, allowing switching capacity to be increased with demand. The Switch Resource Management (SRM) feature allows the hardware table size to be changed, so that switch functions can be optimized based on the use of the switch. There are 3 modes: IP Mode, LAN Mode, and L2 VPN Mode, which modify the size of the Layer 2 and 3 tables for optimum efficiency.

Security, Performance & Availability

The DGS-3630 Series provides a complete set of security features including multi-layer Access Control Lists (ACLs) and 802.1X user authentication via TACACS+ and RADIUS. The DGS-3630 Series also offers extensive VLAN support, including GVRP and 802.1Q VLAN to enhance security and performance. A robust set of QoS features help ensure that critical network services such as Voice over IP and video conferencing are given high priority through the network. The D-Link Safeguard Engine increases the switch's reliability, serviceability, and availability by preventing malicious flooding traffic caused by worms or virus attacks.

D-Link Green Technology

The DGS-3630 Series features D-Link Green technology, which includes a power-saving mode, smart fan feature, reduced heat dissipation, and cable length detection. The power-saving feature automatically powers down ports that have no link or link partner, and ensures that LEDs are shut off when not needed. The smart fan³ feature allows for the built-in fans to automatically turn on only at a certain temperature, providing continuous, reliable, and eco-friendly operation of the switch.

Versatile Management

The DGS-3630 Series provides the D-Link Network Assistant Utility, an industry-standard CLI, and an intuitive web-based management interface that enables administrators to set up and remotely manage their networks. Support for SNMP allows centralized management of a large number of devices and out-of-band management is available via a dedicated console port. A mini-USB console port allows the DGS-3630 Series to be managed without any extra connectors, and a USB Type A port can be used to store logs, configuration, and firmware images. The DHCP auto-configuration and auto-image features can also be used to deploy multiple switches automatically, saving costs for mass deployment.

Technical Specifications

General	DGS-3630-28SC	DGS-3630-28TC	DGS-3630-52TC
Size	• 19-inch, 1U rack-mount size		
Interfaces	<ul style="list-style-type: none"> • 20 SFP ports • 4 Combo 10/100/1000BASE-T/SFP ports • 4 10 GbE SFP+ ports 	<ul style="list-style-type: none"> • 20 10/100/1000BASE-T ports • 4 Combo 10/100/1000BASE-T/SFP ports • 4 10 GbE SFP+ ports 	<ul style="list-style-type: none"> • 44 10/100/1000BASE-T ports • 4 Combo 10/100/1000BASE-T/SFP ports • 4 10 GbE SFP+ ports
Console Port	<ul style="list-style-type: none"> • RJ45 and Mini USB console ports for out-of-band CLI management 		
Management Port	<ul style="list-style-type: none"> • 10/100/1000BASE-T RJ-45 Ethernet for out-of-band IP management 		
Alarm Port	<ul style="list-style-type: none"> • 1 RJ-45 port 		
USB Port	<ul style="list-style-type: none"> • 1 USB 2.0 Type A port 		
Performance			
Switching Capacity	<ul style="list-style-type: none"> • 128 Gbps 	<ul style="list-style-type: none"> • 128 Gbps 	<ul style="list-style-type: none"> • 176 Gbps
Packet Forwarding Rate	<ul style="list-style-type: none"> • 95.24 Mpps 	<ul style="list-style-type: none"> • 95.24 Mpps 	<ul style="list-style-type: none"> • 130.95 Mpps
Packet Buffer	<ul style="list-style-type: none"> • 4 MBytes 		
MAC Address Table	<ul style="list-style-type: none"> • 68K entries² 		
IPv4 Routing Table	<ul style="list-style-type: none"> • 16K entries 		
IPv6 Routing Table	<ul style="list-style-type: none"> • 7K entries 		
IPv4 Forwarding Table	<ul style="list-style-type: none"> • 32K entries² 		
IPv6 Forwarding Table	<ul style="list-style-type: none"> • 16K entries² 		
Jumbo Frame Size	<ul style="list-style-type: none"> • 12 KBytes 		
Physical			
MTBF	<ul style="list-style-type: none"> • 280,612.09 hours 	<ul style="list-style-type: none"> • 300,190.46 hours 	<ul style="list-style-type: none"> • 263,936.78 hours
Acoustics	<ul style="list-style-type: none"> • 56 dB(A) 	<ul style="list-style-type: none"> • 52.7 dB(A) 	<ul style="list-style-type: none"> • 53.9 dB(A)
Heat Dissipation	<ul style="list-style-type: none"> • 216.81 BTU/h 	<ul style="list-style-type: none"> • 144.58 BTU/h 	<ul style="list-style-type: none"> • 212 BTU/h
Power Input	<ul style="list-style-type: none"> • 100 to 240 VAC 50/60 Hz 		
Maximum Power Consumption	<ul style="list-style-type: none"> • 63.58 W 	<ul style="list-style-type: none"> • 42.4 W 	<ul style="list-style-type: none"> • 62 W
Standby Power Consumption	<ul style="list-style-type: none"> • 30.1 W 	<ul style="list-style-type: none"> • 28.1 W 	<ul style="list-style-type: none"> • 36 W
Dimensions	<ul style="list-style-type: none"> • 441 x 259.8 x 44 mm (17.4 x 10.2 x 1.73 inches) 		
Weight	<ul style="list-style-type: none"> • 3.79 kg (8.36 lb) 	<ul style="list-style-type: none"> • 3.74 kg (8.25 lb) 	<ul style="list-style-type: none"> • 4.04 kg (8.91 lb)
Ventilation	<ul style="list-style-type: none"> • 2 x smart fans³ 		
Operating Temperature	<ul style="list-style-type: none"> • -5 to 50 °C (23 to 122 °F) 		
Storage Temperature	<ul style="list-style-type: none"> • -40 to 70 °C (-40 to 158 °F) 		
Operating Humidity	<ul style="list-style-type: none"> • 10% to 95% RH 		
Storage Humidity	<ul style="list-style-type: none"> • 5% to 95% RH 		
Safety Certifications	<ul style="list-style-type: none"> • cUL, CB, CE, CCC, BSMI 		
EMI/EMC	<ul style="list-style-type: none"> • CE, FCC Class A, C-Tick, VCCI, BSMI, CCC 		

Software Features		
Stackability	<ul style="list-style-type: none"> Physical Stacking <ul style="list-style-type: none"> Up to 80 Gbps stacking bandwidth Up to 9 switches in a stack Ring/chain topology support 	<ul style="list-style-type: none"> Virtual Stacking/Clustering of up to 32 units Supports D-Link Single IP Management Up to 20 Gbps stacking bandwidth
L2 Features	<ul style="list-style-type: none"> MAC Address Table : up to 68K entries² Flow Control <ul style="list-style-type: none"> 802.3x Flow Control when using Full Duplex HOL Blocking Prevention Spanning Tree Protocol <ul style="list-style-type: none"> 802.1D STP 802.1w RSTP 802.1s MSTP Root Guard Loop Guard Jumbo Frame: up to 12 KBytes 802.1AX Link Aggregation <ul style="list-style-type: none"> Max. 32 groups per device, 8 ports per group 	<ul style="list-style-type: none"> ERPS (Ethernet Ring Protection Switching) version 2 Port Mirroring <ul style="list-style-type: none"> Supports One-to-One, Many-to-One, Supports Mirroring for Tx/Rx/Both Supports 4 mirroring groups Flow Mirroring <ul style="list-style-type: none"> Supports Mirroring for Rx VLAN Mirroring RSPAN L2 Protocol Tunneling
VLAN	<ul style="list-style-type: none"> 802.1Q 802.1v Protocol-based VLAN Double VLAN (Q-in-Q) <ul style="list-style-type: none"> Port-based Q-in-Q Selective Q-in-Q Port-based VLAN MAC-based VLAN Subnet-based VLAN Private VLAN 	<ul style="list-style-type: none"> VLAN Group <ul style="list-style-type: none"> Max. 4K VLAN groups Max. 4096 VIDs Multicast VLAN (ISM VLAN for IPv4/IPv6) Voice VLAN Auto Surveillance VLAN VLAN Trunking GVRP: Up to 4K dynamic VLANs Asymmetric VLAN
L2 Multicast	<ul style="list-style-type: none"> MLD Snooping <ul style="list-style-type: none"> MLD v1/v2 Snooping Supports up to 4K MLD groups² Host-based MLD Snooping Fast Leave Supports 64 static MLD groups MLD Snooping Querier Per VLAN MLD Snooping MLD Proxy Reporting 	<ul style="list-style-type: none"> IGMP Snooping <ul style="list-style-type: none"> IGMP v1/v2/v3 Supports up to 8K MLD groups² Supports 64 static IGMP groups Per VLAN IGMP Snooping IGMP Snooping Querier Host-based IGMP Snooping Fast Leave PIM Snooping
L3 Features	<ul style="list-style-type: none"> IPv4 ARP/IPv6 ND: support up to 32K/16K² <ul style="list-style-type: none"> 512 Static ARP Gratuitous ARP IP Interface <ul style="list-style-type: none"> Supports 256 interfaces Loopback Interface Proxy ARP <ul style="list-style-type: none"> Support local ARP proxy 	<ul style="list-style-type: none"> IPv6 Tunneling <ul style="list-style-type: none"> Static ISATAP GRE 6to4 VRRP v2/v3 IP Helper
L3 Routing	<ul style="list-style-type: none"> Supports 16K hardware routing entries shared by IPv4/IPv6 <ul style="list-style-type: none"> 1 entry consumed by each IPv4 route 2 entries consumed by each IPv6 route Supports up to 32K hardware L3 forwarding entries shared by IPv4/IPv6² <ul style="list-style-type: none"> 1 entry consumed by each IPv4 route 2 entries consumed by each IPv6 route Static Route <ul style="list-style-type: none"> Max. 512 IPv4 entries Max. 256 IPv6 entries IPv4/IPv6 Default Route 	<ul style="list-style-type: none"> PBR (Policy-based Route) Null Route Route Preference Route Redistribution Graceful Restart (GR) Helper BFD (Bidirectional Forwarding Detection) <ul style="list-style-type: none"> IPv4/v6 Static Route RIP VRRP RIPv1/v2/ng
L3 Multicast	<ul style="list-style-type: none"> IGMP/MLD Filtering 	

QoS (Quality of Service)	<ul style="list-style-type: none"> • 802.1p • 8 queues per port • Queue Handling <ul style="list-style-type: none"> • Strict Priority (SP) • Weighted Round Robin (WRR) • Strict + WRR • Weighted Deficit Round Robin (WDRR) • Congestion Control <ul style="list-style-type: none"> • Weighted Random Early Detection (WRED) • 802.1Qbb Priority-based Flow Control (PFC) for 10GbE port • Bandwidth Control <ul style="list-style-type: none"> • Port-based (Ingress/Egress, min. granularity 8 Kb/s) • Flow-based (Ingress/Egress, min. granularity 8 Kb/s) • Per queue bandwidth control (min. granularity 8 Kb/s) • Policy Map <ul style="list-style-type: none"> • Remark 802.1p priority • Remark IP precedence/DSCP • Time based QoS 	<ul style="list-style-type: none"> • CoS based on: <ul style="list-style-type: none"> • Switch Port • Inner/ outer 802.1p Priority • Inner/ outer VID • MAC address • Ether Type • IP address • ToS/IP Preference • DSCP • Protocol Type • TCP/UDP port • IPv6 Traffic Class • IPv6 Flow Label • Three Color Marker <ul style="list-style-type: none"> • trTCM • srTCM
ACL (Access Control List)	<ul style="list-style-type: none"> • ACL based on: <ul style="list-style-type: none"> • 802.1p priority • VID • MAC address • EtherType • LLC • VLAN • IP address • IP preference/ToS • DSCP mask • Protocol type • TCP/UDP port number • IPv6 Traffic Class • IPv6 Flow Label 	<ul style="list-style-type: none"> • Max. ACL entries: <ul style="list-style-type: none"> • Ingress (hardware entries): 4K • Egress (hardware entries): 1K • VLAN Access Map Numbers: 3K • Time-based ACL
Green	<ul style="list-style-type: none"> • Energy Efficiency Ethernet (EEE) • Power Saving By Link Status • Power Saving By Cable Length 	<ul style="list-style-type: none"> • Power Saving By LED Shut-Off • Power Saving By Port Shut-Off • Power Saving By System Hibernation
Security	<ul style="list-style-type: none"> • Port Security <ul style="list-style-type: none"> • Supports up to 12K MAC addresses per port/VLAN/system • Broadcast/Multicast/Unicast Storm Control • D-Link Safeguard Engine • DHCP Server Screening • Dynamic ARP Inspection • IP Source Guard • DHCP Snooping • IPv6 Snooping • Dynamic ARP Inspection (DAI) • DHCPv6 Guard • IPv6 Route Advertisement (RA) Guard • IPv6 ND Inspection • Duplicate Address Detection (DAD) 	<ul style="list-style-type: none"> • ARP Spoofing Prevention <ul style="list-style-type: none"> • Max. 64 entries • L3 Control Packet Filtering • Unicast Reverse Path Forwarding (URPF) • Traffic Segmentation • SSL <ul style="list-style-type: none"> • Supports TLS 1.0/1.1 • Supports IPv4/IPv6 access • SSH <ul style="list-style-type: none"> • Supports SSH v2 • Supports IPv4/IPv6 access • BPDU Attack Prevention • DOS Attack Prevention • NetBIOS/NetBEUI filtering

AAA	<ul style="list-style-type: none"> • 802.1X Authentication • Supports Port/Host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Bandwidth Control Assignment • ACL Assignment • Web-based Access Control (WAC) • Supports Port/Host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Bandwidth Control Assignment • ACL Assignment • Support IPv4/IPv6 access • Support HTTPS • Compound Authentication 	<ul style="list-style-type: none"> • MAC-based Access Control (MAC) • Supports Port/Host-based access control • Identity-driven Policy Assignment • Dynamic VLAN Assignment • Bandwidth Control Assignment • ACL Assignment • Guest VLAN • Microsoft® NAP <ul style="list-style-type: none"> • Support 802.1X NAP • Support DHCP NAP • Privilege Level for Management Access • RAIDUS and TACACS+ Authentication • Authentication Database Failover • RADIUS/TACACS+ Accounting
OAM (Operations, Administration, and Maintenance)	<ul style="list-style-type: none"> • Cable Diagnostics • 802.3ah Ethernet Link OAM • D-Link Unidirectional Link Detection (DULD) • Dying gasp 	<ul style="list-style-type: none"> • 802.1ag Connectivity Fault Management (CFM) • Y.1731 OAM • Optical Transceiver Digital Diagnostic Monitoring (DDM)
Management	<ul style="list-style-type: none"> • NTPv3/v4 • Precision Time Protocol (PTP) • Web-based GUI <ul style="list-style-type: none"> • Support IPv4/IPv6 access • Support SSL (HTTPS) • Command Line Interface (CLI) • Telnet Server for IPv4/IPv6 access • Telnet Client for IPv4/IPv6 • SNMP <ul style="list-style-type: none"> • Support v1/v2c/v3 • Support IPv4/IPv6 access • SNMP Trap • TFTP Client for IPv4/IPv6 • FTP Client for IPv4/IPv6 • IPv4 SFTP Server • RCP • System Log for IPv4/IPv6 Syslog Server • SMTP • RMONv1 <ul style="list-style-type: none"> • Supports 1,2,3,9 groups • RMONv2 <ul style="list-style-type: none"> • Supports ProbeConfig group 	<ul style="list-style-type: none"> • Command Logging • LLDP/LLDP-MED • D-Link Discover Protocol (DDP) • DHCP Client option 12 • DHCP Auto-configuration • DHCP Auto-image • DHCP Relay option 60/61/62/18/37/125 • DHCP/DCHPv6 Local Relay • DHCP Server <ul style="list-style-type: none"> • Support IPv4/IPv6 address assignment • DHCPv6 Prefix Delegation (PD) • Multiple Images/ Multiple Configurations • DNS Relay for IPv4/IPv6 • DNS Client for IPv4/IPv6 • Debug Command • Password Recovery/ Encryption • Ping/Traceroute for IPv4/IPv6 • Microsoft® Network Load Balancing (NLB) • Switch Resource Management (SRM) • sFlow • D-Link License Management System (DLMS)
Enhanced Image (EI) Features		
VLAN	<ul style="list-style-type: none"> • Super VLAN 	
L3 Routing	<ul style="list-style-type: none"> • BGP <ul style="list-style-type: none"> • BGPv4/v4+ • 4bytes AS • Text/MD5 for BGPv4 • VRF-Lite <ul style="list-style-type: none"> • IPv4 Static Route • RIPv1/v2 • OSPFv2 • BGPv4 	
L3 Multicast	<ul style="list-style-type: none"> • IGMPv1/v2/v3 • MLDv1/v2 • IGMP/MLD Proxy • DVMPv3 	
	<ul style="list-style-type: none"> • Bidirectional Forwarding Detection (BFD) for OSPF • OSPF <ul style="list-style-type: none"> • OSPF v2/v3 • OSPF passive interface • Stub/NSSA area • OSPF equal cost route • Text/MD5 for OSPFv2 	
	<ul style="list-style-type: none"> • PIM-DM/SM/SSM/SDM • SSM Mapping for IPv4/IPv6 • Multicast Source Discovery Protocol (MSDP) 	

MPLS Image (MI) Features

L3 Routing	<ul style="list-style-type: none"> IS-IS v4/v6 	
MPLS	<ul style="list-style-type: none"> Label Distribution Protocol (LDP) PHP (Penultimate hop popping) Virtual Private Wire Service (VPWS) Virtual Private LAN Service (VPLS) 	<ul style="list-style-type: none"> BGP/MPLS VPN Multiprotocol extensions for BGP4 Virtual Routing Forwarding (VRF) LSP/VCCV/MPLS Ping/Traceroute

MIB/IETF Standards

	<ul style="list-style-type: none"> RFC1065, RFC1066, RFC1155, RFC1156, RFC2578 MIB Structure RFC1212 Concise MIB Definitions RFC1213 MIBII RFC1215 MIB Traps Convention RFC1493, RFC4188 Bridge MIB RFC1157, RFC2571, RFC2572, RFC2573, RFC2574, RFC2575, RFC2576 SNMP MIB RFC1442, RFC1901, RFC1902, RFC1903, RFC1904, RFC1905, RFC1906, RFC1907, RFC1908, RFC2578, RFC3418, RFC3636 SNMPv2 MIB RFC271, RFC1757, RFC2819 RMON MIB RFC2021 RMONv2 MIB RFC1398, RFC1643, RFC1650, RFC2358, RFC2665, RFC3635 Ether-like MIB RFC2668 802.3 MAU MIB RFC2674, RFC4363 802.1p MIB Interface Group MIB RFC2618 RADIUS Authentication Client MIB RFC4022 MIB for TCP RFC4113 MIB for UDP RFC2620 RADIUS Accounting Client MIB RFC2925 Ping & TRACEROUTE MIB TFTP uploads and downloads (D-Link MIB) Trap MIB (D-Link MIB) RFC4293 IPv6 MIB RFC4293 ICMPv6 MIB Entity MIB RIPv2 MIB OSPF MIB IPv4 Multicast Routing MIB PIM MIB for IPv4 IP Forwarding Table MIB 	<ul style="list-style-type: none"> RFC4293 IPv6 SNMP Mgmt Interface MIB DDM MIB (D-Link MIB) Private MIB MIB for D-Link Zone Defense DDP MIB LLDP-MED MIB RFC791 IP RFC768 UDP RFC793 TCP RFC792 ICMPv4 RFC2463, RFC4443 ICMPv6 RFC826 ARP RFC1338, RFC1519 CIDR RFC2474, RFC3168, RFC3260 Definition of the DS Field in the IPv4 and IPv6 Headers RFC1321, RFC2284, RFC2865, RFC2716, RFC1759, RFC3580, RFC3748 Extensible Authentication Protocol (EAP) RFC2571 SNMP Framework RFC2572 SNMP Message Processing and Dispatching RFC2573 SNMP Applications RFC2574 User-based Security Model for SNMPv3 RFC1981 Path MTU Discovery for IPv6 RFC2460 IPv6 RFC2461, RFC4861 Neighbor Discovery for IPv6 RFC2462, RFC4862 IPv6 Stateless Address Auto-configuration RFC2464 IPv6 over Ethernet and definition RFC2767 Dual Stack Hosts using the 'Bump-In-the-Stack' Technology RFC3513, RFC4291 IPv6 Addressing Architecture RFC2893, RFC4213 IPv4/IPv6 dual stack function RFC3484 Default Address Selection for Internet Protocol version 6
--	---	---

Ordering Information

Part Number	Description
DGS-3630-28SC/SI	20 SFP ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image ¹
DGS-3630-28SC/EI	20 SFP ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image ¹
DGS-3630-28SC/MI	20 SFP ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image ¹
DGS-3630-28TC/SI	20 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image ¹
DGS-3630-28TC/EI	20 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image ¹
DGS-3630-28TC/MI	20 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image ¹
DGS-3630-52TC/SI	44 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Standard Image ¹
DGS-3630-52TC/EI	44 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with Enhanced Image ¹
DGS-3630-52TC/MI	44 10/100/1000BASE-T ports + 4 Combo 10/100/1000BASE-T/SFP ports + 4 10 GbE SFP+ ports L3 Stackable Managed Switch with MPLS Image ¹

Optional License Upgrades

DGS-3630-28SC-SE-LIC	DGS-3630-28SC Standard Image to Enhanced Image License
DGS-3630-28SC-EM-LIC	DGS-3630-28SC Enhanced Image to MPLS Image License
DGS-3630-28SC-SM-LIC	DGS-3630-28SC Standard Image to MPLS Image License
DGS-3630-28TC-SE-LIC	DGS-3630-28TC Standard Image to Enhanced Image License
DGS-3630-28TC-EM-LIC	DGS-3630-28TC Enhanced Image to MPLS Image License
DGS-3630-28TC-SM-LIC	DGS-3630-28TC Standard Image to MPLS Image License
DGS-3630-52TC-SE-LIC	DGS-3630-52TC Standard Image to Enhanced Image License
DGS-3630-52TC-EM-LIC	DGS-3630-52TC Enhanced Image to MPLS Image License
DGS-3630-52TC-SM-LIC	DGS-3630-52TC Standard Image to MPLS Image License

Optional Management Software

DV-700-N25-LIC	D-View 7 - 25 Node License
DV-700-N50-LIC	D-View 7 - 50 Node License
DV-700-N100-LIC	D-View 7 - 100 Node License
DV-700-N250-LIC	D-View 7 - 250 Node License
DV-700-N500-LIC	D-View 7 - 500 Node License
DV-700-N1000-LIC	D-View 7 - 1000 Node License
DV-700-P5-LIC	D-View 7 - 5 Probe License
DV-700-P10-LIC	D-View 7 - 10 Probe License
DV-700-P25-LIC	D-View 7 - 25 Probe License
DV-700-P50-LIC	D-View 7 - 50 Probe License
DV-700-P100-LIC	D-View 7 - 100 Probe License

Optional 10 Gbps SFP+ Transceivers

DEM-431XT	10GBASE-SR Multi-mode, OM1:33M/OM2:82M/OM3:300M (w/o DDM)
DEM-431XT-DD	10GBASE-SR Multi-mode, OM1:33M/OM2:82M/OM3:300M (with DDM)
DEM-432XT	10GBASE-LR Single-mode, 10 km (w/o DDM)
DEM-432XT-DD	10GBASE-LR Single-mode, 10 km (with DDM)
DEM-433XT	10GBASE-ER Single-mode, 40 km (w/o DDM)
DEM-433XT-DD	10GBASE-ER Single-mode, 40 km (with DDM)
DEM-434XT	10GBASE-ZR Single-mode, 80 km (w/o DDM)
DEM-435XT	10GBASE-LRM Multi-mode, 200 m (w/o DDM)
DEM-435XT-DD	10GBASE-LRM Multi-mode, 200 m (with DDM)
DEM-436XT-BXD	10GBASE-LR Single-mode, 20 km (TX-1330/RX-1270 nm) (w/o DDM)
DEM-436XT-BXU	10GBASE-LR Single-mode, 20 km (TX-1270/RX-1310 nm) (w/o DDM)

DGS-3630 Series Layer 3 Stackable Managed Switches

Optional 1 Gbps SFP Transceivers

DGS-712	1000BASE-T Copper SFP Transceiver
DEM-210	100BASE-FX Single-mode, 15 km
DEM-302S-LX	1000BASE-LX Single-mode, 2 km
DEM-310GT	1000BASE-LX Single-mode, 10 km
DEM-311GT	1000BASE-SX Multi-mode, 550 m
DEM-312GT2	1000BASE-SX Multi-mode, 2 km
DEM-314GT	1000BASE-LHX Single-mode, 50 km
DEM-315GT	1000BASE-ZX Single-mode, 80 km
DEM-220T	100BASE-BX-D Single-mode, 20 km (TX-1550/RX-1310 nm) 100BASE-BX-U Single-mode, 20 km (TX-1310/RX-1550 nm)
DEM-220R	100BASE-BX-U Single-mode, 20 km (TX-1310/RX-1550 nm)
DEM-302S-BXD	1000BASE-BX-D Single-mode, 2 km (TX-1550/RX-1310 nm)
DEM-302S-BXU	1000BASE-BX-U Single-mode, 2 km (TX-1310/RX-1550 nm)
DEM-330T	1000BASE-BX-D Single-mode, 10 km (TX-1550/RX-1310 nm)
DEM-330R	1000BASE-BX-U Single-mode, 10 km (TX-1310/RX-1550 nm)
DEM-331T	1000BASE-BX-D Single-mode, 40 km (TX-1550/RX-1310 nm)
DEM-331R	1000BASE-BX-U Single-mode, 40 km (TX-1310/RX-1550 nm)

Optional 10 Gbps SFP+ Direct Attach Cables

DEM-CB100S	10 GbE SFP+ 1 m Direct Attach Cable
DEM-CB300S	10 GbE SFP+ 3 m Direct Attach Cable
DEM-CB700S	10 GbE SFP+ 7 m Direct Attach Cable

Optional Redundant Power Supplies

DPS-500A	AC Redundant Power Supply
DPS-500DC	DC Redundant Power Supply

¹ Stacking cable and USB flash card not included.

² Based on maximum value of Switch Resource Management (SRM).

³ By default, the fan speed is low. When the temperature inside the chassis is over 36 °C, the fans switch to high speed until the temperature drops below 33 °C.

Updated 2016/03/29