


Teknik Özellikler

| | DEM-310GT | DEM-311GT | DGS-712 |
|---------------------|--------------------------|-------------------------------------|---------------------------|
| Verici Tipi | • SFP | • SFP | • RJ45 |
| Fiber Media Support | • Single-Mode | • Multi-Mode | • N/A |
| Hız | • 1.25 Gbps | • 1 Gbps | • 1 Gbps |
| Mesafe | • 10 km | • 550 m | • 100 m |
| Compliant Standard | • IEEE802.3z 1000BASE-LX | • IEEE802.3z 1000BASE-SX | • IEEE 802.3ab 1000BASE-T |
| Konnetor | • Duplex LC connector | • Duplex LC connector | • RJ45 |
| Single/Bi Direction | • Single-direction | • Single-direction | • N/A |
| Dalgaboyu | • 1310 nm | • 850 nm | • N/A |
| Kablo Tipi | • Single-mode 9 um fiber | • Multi-mode 50 um or 62.5 um fiber | • Cat5, Cat5e, Cat6 |
| Güç | • 3.3V | • 3.3V | • 3.3V |
| Hot Pluggable | ✓ | ✓ | ✓ |
| MSA Uyumlu | ✓ | ✓ | ✓ |
| RoHS Uyumlu | ✓ | ✓ | ✓ |



| | DEM-314GT | DEM-315GT | DEM-330T |
|---------------------|---------------------------|--------------------------|------------------------------|
| Verici Tipi | • SFP | • SFP | • SFP |
| Fiber Media Support | • Single-Mode | • Single-Mode | • Single-Mode |
| Hız | • 1.25 Gbps | • 1 Gbps | • 1.25 Gbps |
| Mesafe | • 50 km | • 80 km | • 10 km |
| Compliant Standard | • IEEE802.3z 1000BASE-LHX | • IEEE802.3z 1000BASE-ZX | • IEEE802.3ah 1000BASE-BX-D |
| Konnetor | • Simplex LC connector | • Simplex LC Connector | • Simplex LC connector |
| Single/Bi Direction | • WDM bi-direction | • WDM bi-direction | • WDM bi-direction |
| Dalgaboyu | • 1550 nm | • 1550 nm | • Tx: 1550 nm Rx: 1310 nm |
| Kablo Tipi | • Single-mode 9 um fiber | • Single-mode 9 um fiber | • Single-mode 9/125 um fiber |
| Güç | • 3.3V | • 3.3V | • 3.3V |
| Hot Pluggable | R | R | R |
| MSA Uyumlu | R | R | R |
| RoHS Uyumlu | R | R | R |

DEM-DGS Serisi Gigabit SFP Vericiler

| Sipariş Bilgileri | | |
|-------------------|--|--|
| Model İsmi | Açıklama | |
| DEM-310GT | 1000BASE-LX Single-Mode 10KM SFP Transceiver | |
| DEM-311GT | 1000BASE-SX Multi-Mode 550M SFP Transceiver | |
| DGS-712 | 1000BASE-T Copper 100M SFP Transceiver | |
| DEM-314GT | 1000BASE-LX Single-Mode 10KM SFP Transceiver 1000BASE-SX | |
| DEM-330T | Multi-Mode 550M SFP Transceiver 1000BASE-ZX | |
| DEM-315GT | Single-Mode 80KM SFP Transceiver | |

Güncelleme 2014/04/03

Teknik özellikler önceden bildirilmeksizin değiştirilebilir ©2014 D-Link Corporation/D-Link Systems, Inc. 'in Tüm hakları saklıdır. D-Link, D-Link logosu, Amplifi, MediaBridge, SharePort, D-Link Yeşil, D-Link Yeşil Logosu, Xtreme N, D-Link RoHS logo ve ticari markaları ya da tescilli ticari markaları D-Link Corporation'ın veya yan kuruluşlarının Amerika Birleşik Devletleri ve/veya diğer ülkeler. Diğer ticari markalar veya tescilli ticari markalar ilgili sahiplerinin mülkiyetindedir.

D-Link[®]
Building Networks for People