



DMC-F02SC

10/100Base-TX to 100Base-FX SC Multi-mode Media Converter (2 km)

The DMC-F02SC is a standalone media converter designed to convert a twisted-pair 10/100Base-TX Fast Ethernet connection to a multi-mode fiber 100Base-FX Fast Ethernet connection, that allows to extend a connection distance (up to 2 km) between two devices. This media converter is equipped with one RJ-45 for twisted-pair and one fiber optic SC port.

Technical Specifications	
Hardware	
Interfaces	<ul style="list-style-type: none"> One 10/100Base-TX port One 100Base-FX SC port
LEDs	<ul style="list-style-type: none"> PWR Link/Act (SC) Link/Act (RJ-45)
Functionality	
Standards and Functions	<ul style="list-style-type: none"> IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX IEEE 802.3u 100Base-FX Auto MDI/MDIX adjustment for copper port
Maximum Packet Size	<ul style="list-style-type: none"> 16 KB
Physical Parameters	
Dimensions (L x W x H)	<ul style="list-style-type: none"> 70.5 x 93.5 x 26 mm
Weight	<ul style="list-style-type: none"> 134 g
Environmental Conditions	
Power Supply	<ul style="list-style-type: none"> 5 V DC, 0.55 A power adapter
Max. Power Consumption	<ul style="list-style-type: none"> 1.5 W
Wavelength	<ul style="list-style-type: none"> 1310 nm
Length of Supported Fiber Optic Cable	<ul style="list-style-type: none"> Up to 2 km
Temperature	<ul style="list-style-type: none"> Operating: 0 to 55 °C Storage: -25 to 70 °C
Humidity	<ul style="list-style-type: none"> 20% to 80% non-condensing
Order Information	
<i>Part Number</i>	<i>Description</i>
DMC-F02SC	10/100Base-TX to 100Base-FX SC Multi-mode Media Converter (2 km)